

UFH-0405CDHC04: 4-groups manif.comp. h/c, adjustable with flow meter



Commercial information

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility



Technical characteristics

Connection type primary side	2-pipe	Number of floor heating groups	4
Connection central heating	External thread	Max. operating pressure	4 Bar
Suitable for cooling	Yes	Max. number of expansion groups	0
Material	Plastic	Width	150 Millimetre
Nominal diameter central heating	DN 15	Height	470 Millimetre
Position primary connection	Bottom	Depth	510 Millimetre
Nominal diameter primary connection	1/2 inch (15)		
With valves on primary connection	No		
Expandable	No		
Hydraulic balance control	None		
With thermometer	Yes		
Temperature measurement supply	Analogue		
Temperature measurement return	Analogue		
With de-aeration	No		
With pressure gauge	No		
With filling/drain tap	Yes		
Closable groups	Yes		
With flow-through indicator	Yes		
With wall-mounting bracket	Yes		
With casing	No		

Related products

Product code	GTIN	Description
BE50	05414764221376	Henco Jaws (universal) BE-Profile 50x4

Image

UFH-C190118 05414764221376 Henco Flowmeter 0-480 L/H Adjustable For CD UFH-TM050-M 05414764221376 Henco Thermometer for return with EK connections