UFH-TACK-A: Tacker gun for UFH-TACK-40 and UFH-TACK-60



Commercial information

Tacker gun for UFH-TACK-40 and UFH-TACK-60

Lighter, smarter and more stable: designed for maximum ease of use on every jobsite and optimum ergonomics for the installer.

Lighter
- Thanks to the combination of aluminium in the base unit, polyamide in the guide rail and polypropylene for the remaining plastic components, the tacker gun is lightweight while also being exceptionally robust.

Smarter
- The weight that presses the tacker staples downwards is permanently attached to the guide rail. This prevents it from being accidentally removed or lost on site.
- There are no cables between the various components, which increases ease of use.
- The guide rail is designed so that tacker staples can only be loaded from the top. This prevents them from falling out of the rail, even when the tool is held at an angle. In addition, the guide rail is firmly connected to the body of the tacker gun.
- The inspection hatch has been designed for extra durability and opens at an angle, significantly reducing the risk of breakage. Jammed tacker staples can therefore be removed quickly and easily.
- Both Henco UFH-TACK-40 and UFH-TACK-60 tacker staples are compatible with this tool, as well as other tacker staples with a width of 6 mm.

More stable
- Thanks to the optimal weight distribution, with a low centre of gravity in the lower part of the tool, pipes can be fixed accurately and effortlessly.
- The integrated stand keeps the tacker gun stably upright, allowing the installer to work more comfortably, safely and efficiently.

Basic unit dimensions	
Height	925 mm
Length	245 mm
Width	235 mm
Net weight	1.700 kg

Certificates

Applications

Underfloor Heating

Solutions

Underfloor heating, Building installations, Utility, Industry

Technical characteristics

Magazine capacity	105	
Suitable for pipe diameter	16|20	Millimetre
Anchor clip length	43|58	Millimetre
Height	925	Millimetre
Width	235	Millimetre