

PIXO LINE DRIVER DALI 600 BLACK  
0007868



Features

• Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Constant current 350mA -1050mA digital dimmable DALI in-track driver with GR6d-15 connector for LED light modules, polycarbonate body Clip holder and fixing screw included in the driver box, black finishing colour, max. system power: 56W, operating voltage: 220-240V / 50-60Hz Driver module should be combined with suitable LED module. Switch-dim selection with 8 power settings meet all installation needs with one single product selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class I. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.672mmx32mmx31mm

Product Overview

Product name	PIXO LINE DRIVER DALI 600 BLACK
Technology	LED
Mount	Ceiling surface mounting
General application	Retail, Hospitality, Museums & Galleries, Office
ETIM Class	EC002710
E-number FI	4279421
Light colour	N/A
Photobiological Risk Group	Not applicable
Total power consumption (W)	56

PIXO LINE DRIVER DALI 600 BLACK  
0007868

Electrical protection	Class I
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Black
IP rating	IP20
IK rating	IK03
Product EAN number	5410288078687
Warranty	5 years
Dimming method	DALI

Technical drawings

