




Color: ■ gray Similar to illustration

Electrical data	
Operating voltage	250 VAC
Power (max.)	0.6 W
Thermal resistance	140 K/W
Tolerance	±1%
Resistor type/design	DIN 0207

Safety and protection	
Rated surge voltage	4 kV
Pollution degree	3
Protection type	IP20

Connection data	
Connection points	4
Total number of potentials	1
Number of levels	1
Connection technology	CAGE CLAMP®
Actuation type	Operating tool
Connectable conductor materials	Copper Aluminum
Solid conductor	0.08 ... 4 mm² / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 4 mm² / 28 ... 12 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 inches



Physical data	
Width	6 mm / 0.236 inches
Height	86 mm / 3.386 inches
Depth from upper-edge of DIN-rail	29 mm / 1.142 inches

Material data	
Color	gray
Insulation material	Polyamide (PA66)
Material group	I
Flammability class per UL94	V0
Fire load	0.322 MJ
Weight	13.5 g

Environmental requirements	
Ambient temperature (operation)	-25 ... +70 °C

Standards and specifications	
Standards/specifications	EN 60947-7-1 EN 60664-1 EN 60569

Commercial data	
PU (SPU)	50 pcs
Country of origin	DE
GTIN	4055143563925
Customs tariff number	85369010000

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
281-665/281-979