

29P-1612-CS: Press-fit adapter with copper pipe 16x12 CuSi



Commercial information

Deze persfitting verlengd met een stuk koperen buis (50mm) is de perfecte oplossing om van een bestaande installatie in koper over te schakelen naar een Henco oplossing met meerlagenbuis.

Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, Sans 21003, Kontrol Biro, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	16 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	12 Millimetre
Material connection 2	Copper	Length	92 Millimetre
Material quality connection 2	Dezincification resistant brass (DZR)	Length of connection 1	30 Millimetre
Surface protection connection 2	Untreated	Working length connection 1	30 Millimetre
Surface treatment connection 2	Untreated	Length of connection 2	50 Millimetre
Shape	Straight	Working length connection 2	50 Millimetre
Reducing	✗	Wrench width	0 Millimetre
Eccentric	✗	Wrench width union nut	0 Millimetre
System specific	✓	Tightening moment	0 0 Newtonmetre
Connection 1	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
Contour code connection 1	TH	Max. operating pressure at 20 °C	16 Bar
Connection 2	Soldered end	Max. operating pressure at max. medium temperature	10 Bar
Contour code connection 2	V		
Main colour fitting	Grey		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✗		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✗		
Capped	✗		
With connection indicator	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		

Related products

Product code	GTIN	Description
BE16MINI3	05414764368910	Henco Jaw for press machine M-BMINI3 BE/TH-Profile 16mm

Image

