

## 29P-2622-CS: Press adapter with copper pipe 26x22 cusi



### Commercial information

The body of the fitting is made from CW724R brass. These fittings offer great advantages with regard to corrosion and they are also also better for the environment.

- The fitting has a buffer ring that prevents direct galvanic contact between the aluminium of the pipe and the brass of the fitting.
- This excludes the possibility of electrolysis occurring.
- The fitting is equipped with O-rings made from EPDM and RVS pressure sleeves with 3 inspection windows.
- In order to prevent assembly errors, the dimensions and type of press profile which can be pressed are shown on the RVS sleeves

### Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, EMI

### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Surface protection connection 1	Nickel-plated	Outer pipe diameter connection 1	26 Millimetre
Material connection 2	Copper	Outer pipe diameter connection 2	22 Millimetre
Material quality connection 2	Dezincification resistant brass (DZR)	Length	89 Millimetre
Surface protection connection 2	Nickel-plated	Length of connection 1	30 Millimetre
Shape	Straight	Working length connection 1	30 Millimetre
Reducing	✘	Length of connection 2	67 Millimetre
Eccentric	✘	Working length connection 2	67 Millimetre
System specific	✓	Wrench width union nut	0 Millimetre
Connection 1	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
Contour code connection 1	TH	Max. operating pressure at 20 °C	16 Bar
Connection 2	Soldered end	Standard Dimension Ratio (SDR)	0
Contour code connection 2	V		
Main colour fitting	Grey		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
VdS quality mark	✘		
KIWA certified	✓		
Gastec QA mark	✘		

## Related products

Product code	GTIN	Description
BE26MINI3	05414764346277	Henco Jaw for press machine M-BMINI3 BE/TH-Profile 26mm

Image

