


# 2P-2605: Backplate elbow female 26x3/4"





## Commercial information

The body of the fitting is made from CW617N brass. These fittings offer great advantages with regard to corrosion and they are also also better for the environment.

- · The fitting has a buffer ring that prevents direct galvanic contact between the aluminium of the pipe and the brass of the fitting.
- This excludes the possibility of electrolysis occurring.
- The fitting is equipped with O-rings made from EPDM and RVS pressure sleeves with 3 inspection windows.
- In order to prevent assembly errors, the dimensions and type of press profile which can be pressed are shown on the RVS sleeves

#### Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, EMI

### **Applications**

Potable water, Heating, Compressed air, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding



# **Technical characteristics**

Housing material	Brass	Length of connection 1	30.5 Millimetre
Housing material	Brass	Working length connection 1	25 Millimetre
Surface protection	Untreated	Length of connection 2	52 Millimetre
Shape	Right-angled	Working length connection 2	52 Millimetre
Thread size	3/4 inch	Length from wall plate	52 Millimetre
System specific	✓	Length of connection 3	0 Millimetre
Nominal diameter connection 2	3/4 inch (20)	Working length connection 3	0 Millimetre
Connection	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
Thread size tap connection	3/4 inch	Max. operating pressure at 20 °C	16 Bar
Contour code	TH		
DVGW quality mark for gas	×		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	×		
KOMO certified	✓		
Type approval according to BBR/EKS	×		

Related products				
Product code BE26	GTIN 05414764020088	Description Henco Jaws (universal) BE/TH-Profile 26x3	Image	
BL20	03414704029000	Tienco Jaws (universal) DE/TTI-FTOILE 20X3		
PRESSCHECK1432	05414764029088	Henco Tool to control the accuracy of a pressing Ø14-32	*	
PLP-P-PK	05414764029088	Henco Galvanised bracket for backplate elbow		
PLF-P-PK	05414764029088	Henco Galvanised bracket flat for backplate elbow		

