

43P-161516: T-piece Press 16 x compression 15 x Press 16



Commercial information

- Direct connection to Henco press 16 mm in copper or central heating pipe 15 mm
- Short installation length 2 x Press 16 mm x Compression 15 mm

Basic unit dimensions

Height	49 mm
Length	95 mm
Width	26 mm
Net weight	0.139 kg

Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Angle	90 Degrees
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	16 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	15 Millimetre
Material connection 2	Brass	Outer pipe diameter connection 3	16 Millimetre
Surface protection connection 2	Untreated	Wrench width	0 Millimetre
Surface treatment connection 2	Untreated	Max. operating pressure at 20 °C	16 Bar
Material connection 3	Brass	Wrench width union nut	0 Millimetre
Surface treatment connection 3	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Model	T-piece	Standard Dimension Ratio (SDR)	0
Reducing	✘		
System specific	✔		
Connection 1	Press sleeve		
Connection 2	Compression ring		
Connection 3	Press sleeve		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
Main colour fitting	Brass		
High tensile strength	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✔		
With drain valve	✘		
With de-aerator	✘		
With thermal insulation	✘		
With buffer stud	✔		
Capped	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✔		
KIWA certified	✔		
Gastec QA mark	✘		
KOMO certified	✔		
Type approval according to BBR/EKS	✘		