

PRODUCT DATASHEET

Type: eTRACE-HW-PRO
Art. Nr.: 41248



Short description

Self-regulating hot water heating belt, 13 W/m



Product Description

The eTRACE-HW-PRO self-regulating heating tape is used on tanks, pipes, valves and much more for process temperatures between 30 °C and approx. 80 °C. With the exception of the connections, the heating tape may be completely immersed in a liquid. The eTRACE-HW-PRO heating tape is often used to heat grease lines, e.g. in the food industry. However, it is also useful for waste water pipes in canteens and (large) kitchens to prevent the build-up of grease through heating. The heating tape is moisture-proof and UV-resistant, the supply conductors are nickel-plated copper. These self-regulating heating tapes can be easily cut to the required length and used immediately. Max. Ambient temperature: 85 °C switched off, nominal temperature: 65 °C switched on, min. installation temperature: -30°C, min. bending radius: 25 mm, max. heating circuit length at 0 °C/16 A: 75 m, 230V, CE compliant

ETIM characteristics

Cable type	Dual core	Nominal voltage	230 Volt
Constant power	✗	Max. hold temperature	85 Degrees celsius
Self-limiting	✓	Heating capacity	11 Watt per metre
Screening	Braiding	Diameter	0 Millimetre
Material screening	CuNi	Height	6.1 Millimetre
Surface coating screening	None	Width	13.2 Millimetre
Colour	Black	Length	0 Metre
Application	Fluid temperature monitoring		

Created on: 27/06/2025