

Concord

OPTIX SURFACE 1200 MPO D HO 4000K DALI 2021666



Features

- OPTIX SURFACE 1200 MPO D HO 4000K DALI is a high efficacy low glare surface or suspended LED Linear luminaire with Micro Prismatic diffuser, with direct light distribution, luminaire dimensions: 1200x200x50mm, Sylvania White body colour (RAL9016), IP20, IK07, DALI Dimmable, low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 3550lm luminous flux, 31W power consumption, 114lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<20, Luminance at 65° < 3000 cd/m², lifespan: 58,000 hours L90B10, photobiological safety risk group 1. Electrical protection Class I.

Product Overview

Product name	OPTIX SURFACE 1200 MPO D HO 4000K DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	3550
Luminaire efficacy (lm/W)	114
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 20
Photobiological Risk Group	RG1
Total power consumption (W)	31


Concord

OPTIX SURFACE 1200 MPO D HO 4000K DALI

2021666

Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9016
IP rating	IP20
IK rating	IK07
Product EAN number	5025768216666
Warranty	5 years
Dimming method	DALI

Photometry



Technical drawings

