



### Features

- Surface or Suspended LED Linear luminaire with Louvre + Prismatic Optic, Direct Light Distribution, Luminaire Dimensions: 1160x187x47mm, Sylvania White body colour, IP20, IK07, Light Engine Dimensions: 1130x165mm, Constant Current, Low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 5800lm, 52W, 112lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<19, Luminance at 65° < 3000 cd/m<sup>2</sup>, Lumen Maintenance: L90B10 at 50,000 hours, Quick electrical connection with push-connectors in the luminaire, Glow Wire Test 850°C.

### Product Overview

<b>Product name</b>	RANA LED S 1200 HO 3K LOUV+PRI W GEN2
<b>Technology</b>	LED
<b>Cap/Base</b>	N/A
<b>Housing</b>	Steel
<b>Mount</b>	Ceiling surface mounting, Suspended
<b>E-number FI</b>	4273618
<b>Fixture luminous flux (lm)</b>	5800
<b>Luminaire efficacy (lm/W)</b>	112
<b>Colour temperature (K)</b>	3000
<b>Light colour</b>	Warm White
<b>CRI (Ra)</b>	80
<b>Colour Variation Initial (SDCM)</b>	3
<b>Glare control</b>	< 19
<b>Photobiological Risk Group</b>	RG0
<b>Total power consumption (W)</b>	52
<b>Electrical protection</b>	Class I
<b>Control gear type</b>	LED driver constant current
<b>Housing colour</b>	White
<b>IP rating</b>	IP20

Light your world

## RANA LED S 1200 HO 3K LOUV+PRI W GEN2 0051487

IK rating

IK07


Product EAN number

5410288514871


Warranty

5 years

### Photometry



### Technical drawings



Light your world