

Color:  multi-colored

Three-phase set, 285 Series, t-wrench und 8 mm

Enjoy fault-free electrical installations with this three-phase set (item number 285-1165). Strip lengths must be between 45 mm and 47 mm when connecting conductors to this three-phase set. Featuring conductor terminals along with POWER CAGE CLAMP, this product is highly versatile. The POWER CAGE CLAMP is perfect for connecting large conductor cross-sections. This universal connector is both reliable and maintenance-free. What's more, you can use it to connect all types of conductors and the clamping point can be locked open, making it easier to use. You do not need to use a torque wrench or prepare the conductor. For example, crimping ferrules is not necessary. This three-phase set is suitable for conductor cross sections ranging from 50 mm<sup>2</sup> to 185 mm<sup>2</sup>. It has one level. You can connect four potentials using the ten clamping points. The multi-colored housing is made of polyamide (PA66) for insulation.

#### This item includes:

[Item No.: 285-1167](#)

1

[Item No.: 285-1161](#)

3

2-conductor through terminal block; 185 mm<sup>2</sup>; lateral marker slots; with fixing flanges; POWER CAGE CLAMP; 185,00 mm<sup>2</sup>; dark gray-yellow

2-conductor through terminal block; 185 mm<sup>2</sup>; lateral marker slots; with fixing flanges; POWER CAGE CLAMP; 185,00 mm<sup>2</sup>; gray

#### Electrical data

Ratings per		IEC/EN 60947-7-1		
Overvoltage category		III	III	II
Pollution degree		3	2	2
Nominal voltage		1000 V	-	-
Rated surge voltage		12 kV	-	-
Rated current		353 A	-	-

Ratings per IEC/EN 2		
Rated voltage (III/3)	1500 V	
Rated impulse withstand voltage (III/3)	12 kV	

Approvals per			UL 1059		
Use group	B	C	D		
Rated voltage	600 V	600 V	-		
Rated current	310 A	310 A	-		

Approvals per			CSA 22.2 No 158		
Use group	B	C	D		
Rated voltage	1000 V	1000 V	-		
Rated current	310 A	-	-		

**Connection data**

Clamping units	10
Total number of potentials	4
Number of levels	1

**Connection 1**

Connection technology	POWER CAGE CLAMP
Actuation type	T-wrench; 8 mm
Connectable conductor materials	Copper
Nominal cross-section	185 mm <sup>2</sup> / 350 kcmil
Solid conductor	50 ... 185 mm <sup>2</sup> / 1/0 AWG ... 350 kcmil
Stranded conductor	50 ... 185 mm <sup>2</sup> / 1/0 AWG ... 350 kcmil
Fine-stranded conductor	50 ... 185 mm <sup>2</sup> / 1/0 AWG ... 350 kcmil
Fine-stranded conductor; with insulated ferrule	50 ... 150 mm <sup>2</sup> / 1/0 AWG ... 300 kcmil
Fine-stranded conductor; with uninsulated ferrule	50 ... 185 mm <sup>2</sup> / 1/0 AWG ... 350 kcmil
Strip length	45 ... 47 mm / 1.77 ... 1.85 inches
Wiring direction	Side-entry wiring

**Physical data**

Width	128 mm / 5.039 inches
Height from the surface	123 mm / 4.843 inches
Depth	170 mm / 6.693 inches

**Mechanical data**

Design	horizontal type
Mounting type	Mounting flange Panel mounting
Marking level	Side marking

**Material data**

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	multi-colored
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	VO
Fire load	21.784 MJ
Halogen-free	Yes
Weight	2200 g

**Environmental requirements**

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

**Commercial data**

eCl@ss 10.0	27-14-11-06
eCl@ss 9.0	27-14-11-06
ETIM 9.0	EC001284
ETIM 8.0	EC001284
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143657006
Customs tariff number	85369010000

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Approvals / Certificates****General approvals**

Approval	Standard	Certificate Name
CCA	EN 60947	NTR NL 7965
DEKRA Certification B.V.		
CSA	C22.2	154112
DEKRA Certification B.V.		
KEMA/KEUR	EN 60947	71-126013
DEKRA Certification B.V.		
UL	UL 1059	E45172
Underwriters Laboratories Inc.		

**Declarations of conformity and manufacturer's declarations**

Approval	Standard	Certificate Name
EU-Declaration of Conformity	-	-
WAGO GmbH & Co. KG		
UK-Declaration of Conformity	-	-
WAGO GmbH & Co. KG		

**Downloads****Environmental Product Compliance****Compliance Search**

Environmental Product Compliance 285-1165

**Documentation****Additional Information**

Technical Section	pdf 2246.92 KB	
-------------------	-------------------	--

**Bid Text**

285-1165	19.02.2019	xml 4.10 KB	
285-1165	04.01.2018	doc 25.50 KB	

## 1 Compatible Products

### 1.1 Optional Accessories

#### 1.1.1 Cover

##### 1.1.1.1 Cover



[Item No.: 285-1178](#)

Finger guard; touchproof cover protects unused conductor entries and jumper slots; for 185 mm<sup>2</sup> high-current terminal blocks; yellow

#### 1.1.2 Installation

##### 1.1.2.1 Mounting accessories



[Item No.: 285-1179](#)

Fixing element; for 185 mm<sup>2</sup> high-current terminal blocks; orange

#### 1.1.3 Jumper

##### 1.1.3.1 Jumper



[Item No.: 285-1171](#)

Jumper; insulated; gray

#### 1.1.4 Marking

##### 1.1.4.1 Marker



[Item No.: 793-5501/000-006](#)

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; blue

[Item No.: 793-5501/000-014](#)

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; brown

[Item No.: 793-5501/000-007](#)

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; gray

[Item No.: 793-5501/000-023](#)

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; green



[Item No.: 793-5501/000-017](#)

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; light green

[Item No.: 793-5501/000-012](#)

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; orange

[Item No.: 793-5501/000-005](#)

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; red

[Item No.: 793-5501/000-024](#)

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; violet



[Item No.: 793-5501](#)

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white

[Item No.: 793-5501/000-002](#)

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; yellow

[Item No.: 793-501/000-006](#)

WMB marking card; as card; not stretchable; plain; snap-on type; blue

[Item No.: 793-501/000-007](#)

WMB marking card; as card; not stretchable; plain; snap-on type; gray



[Item No.: 793-501/000-023](#)

WMB marking card; as card; not stretchable; plain; snap-on type; green

[Item No.: 793-501/000-017](#)

WMB marking card; as card; not stretchable; plain; snap-on type; light green

[Item No.: 793-501/000-012](#)

WMB marking card; as card; not stretchable; plain; snap-on type; orange

[Item No.: 793-501/000-005](#)

WMB marking card; as card; not stretchable; plain; snap-on type; red

## 1.1.4.1 Marker

[Item No.: 793-501/000-024](#)

WMB marking card; as card; not stretchable; plain; snap-on type; violet

[Item No.: 793-501](#)

WMB marking card; as card; not stretchable; plain; snap-on type; white

[Item No.: 793-501/000-002](#)

WMB marking card; as card; not stretchable; plain; snap-on type; yellow

[Item No.: 2009-115/000-006](#)

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue

[Item No.: 2009-115/000-007](#)

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray

[Item No.: 2009-115/000-023](#)

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green

[Item No.: 2009-115/000-017](#)

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; light green

[Item No.: 2009-115/000-012](#)

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange

[Item No.: 2009-115/000-005](#)

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red

[Item No.: 2009-115/000-024](#)

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet

[Item No.: 2009-115](#)

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

[Item No.: 2009-115/000-002](#)

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow

## 1.1.4.2 Marking strip

[Item No.: 2009-110](#)

Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

## 1.1.5 Power tap

[Item No.: 285-1175](#)

Power tap; for 185 mm<sup>2</sup> high-current terminal blocks; gray

## 1.1.6 Protective warning marker

[Item No.: 285-1177](#)

Protective warning marker; with high-voltage symbol; black; yellow

## 1.1.7 Tool



## 1.1.7.1 Operating tool

[Item No.: 285-172](#)

Allen wrench; with a partially insulated shaft; green

[Item No.: 285-173](#)

Allen wrench; with a partially insulated shaft; with anti-rotation protection; green