

RANA LED S 1200 HO 4K LOUV+PRI W GEN2
0051491



Features

• Surface or Suspended LED Linear luminaire with Louvre + Prismatic Optic, Direct Light Distribution, Luminaire Dimensions: 1160x187x47mm, Sylvania White body colour, IP20, IK07, Light Engine Dimensions: 1130x165mm, Constant Current, Low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 6000lm, 52W, 115lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<19, Luminance at 65° < 3000 cd/m2, Lumen Maintenance: L90B10 at 50,000 hours, Quick electrical connection with push-connectors in the luminaire, Glow Wire Test 850°C.


Product Overview

Product name	RANA LED S 1200 HO 4K LOUV+PRI W GEN2
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
E-number FI	4273665
Fixture luminous flux (lm)	6000
Luminaire efficacy (lm/W)	115
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	52
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	White
IP rating	IP20


RANA LED S 1200 HO 4K LOUV+PRI W GEN2
0051491

IK rating	IK07
Product EAN number	5410288514918
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	RANA LED S 1200 HO 4K LOUV+PRI W GEN2
Technology	LED
Cap/Base	N/A

RANA LED S 1200 HO 4K LOUV+PRI W GEN2 0051491

Housing	Steel
Mount	Ceiling surface mounting, Suspended
Operating temperature range (°C)	5°C...+25°C
Performance ambient temperature Tq (°C)	25
E-number FI	4273665
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	6000
Luminaire efficacy (lm/W)	115
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	52
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	275
Inrush Current (A)	33
Inrush Duration (µs)	250
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	28

RANA LED S 1200 HO 4K LOUV+PRI W GEN2 0051491

Connectable conductor cross section - Min (mm ²)	2.5
---	-----

Connectable conductor cross section - Max (mm ²)	2.5
---	-----

LIFETIME DATA

Lifespan L70 B50	50000
------------------	-------

Lifespan L70 B10	50000
------------------	-------

Lifespan L80 B50	50000
------------------	-------

Lifespan L80 B10	50000
------------------	-------

Lifespan L90 B50	50000
------------------	-------

Lifespan L90 B10	50000
------------------	-------

PHYSICAL DATA

Housing colour	White
----------------	-------

IP rating	IP20
-----------	------

IK rating	IK07
-----------	------

Diffuser finish	Prismatic
-----------------	-----------

Diffuser material	PC Polycarbonate
-------------------	------------------

Nominal Product Length (mm)	1160
-----------------------------	------

Nominal Product Width (mm)	187
----------------------------	-----

Weight (kg)	3.2
-------------	-----

PACKAGING

Single packaging type	Carton
-----------------------	--------

Product EAN number	5410288514918
--------------------	---------------

Packaging single width (cm)	6.5
-----------------------------	-----

Packaging single depth (cm)	21.0
-----------------------------	------

DUN14 (outer)	05410288514918
---------------	----------------

Packaging outer length / height (cm)	153.5
--------------------------------------	-------

SAFETY DATA

Optimal operating condition (°C)	5-25
----------------------------------	------



RANA LED S 1200 HO 4K LOUV+PRI W GEN2
0051491

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No