

Specifications

Photo is representative

Eaton RS2-11-C10

Eaton RS-Titan non-contact door interlock safety switch, Magnetic Reed Switch, Polyamide enclosure, 300 mA max DC, 1 Normally Open and 1 Normally Closed, 300 mA at 24 Vdc, 33 Ft. (10m) Cable, < 10% accuracy, 33 Ft. (10m)

General specifications

PRODUCT NAME	Eaton RS-Titan non-contact door interlock safety switch
CATALOG NUMBER	RS2-11-C10
UPC	786685886367
PRODUCT LENGTH/DEPTH	0.94 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	0.44 in
PRODUCT WEIGHT	0.875 lb
WARRANTY	1 year
COMPLIANCES	CE Marked
CERTIFICATIONS	UL Listed
CATALOG NOTES	0
PRODUCT TYPE	Non-contact door interlock safety switch



Powering Business Worldwide

Product specifications

TYPE	Mechanical Limit Switches
CONTACT RATING	300 mA at 24 Vdc
CABLE TYPE	Polyvinyl Chloride (PVC)
ACCURACY	< 10%
ENCLOSURE MATERIAL	Polyamide
CORD LENGTH	396 ft
CONNECTION	33 ft (10m) cable
CONTACT CONFIGURATION	1 NO-1 NC
SWITCH TYPE	Magnetic reed switch
OPERATING TEMPERATURE - MAX	131 °F
OPERATING TEMPERATURE - MIN	14 °F
ENVIRONMENTAL RATING	IP67, IP69K
MAXIMUM DC CURRENT	300 mA

Resources

CATALOGS	Sensing Solutions, Safety Products, Volume 8, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - RS2-11-C10

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

