

Marking strips; for Smart Printer; permanent adhesive; 15 mm; red



Similar to illustration

Marking method	Thermal transfer
Marking	plain
Delivery form	Roll
Delivery form configuration	20 m; 1 line
Printing device	Smart Printer (thermal transfer printer)

Width	15 mm
Depth	0.2 mm
Strip width	15 mm

Mounting type	Sticking
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Color	red
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	Acrylic; permanent
Halogen-free	Yes
Weight	180 g
Fire load	0 MJ



Environmental requirements	
Ambient temperature (storage)	+10 ... +21 °C
Ambient temperature (operation)	-40 ... +150 °C
Relative humidity	40 ... 50 %

Commercial data	
ETIM 9.0	EC001288
ETIM 8.0	EC001288
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4066966346367
Customs tariff number	39199080888

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 210-702/020-005	

1 Compatible Products
1.1 Optional Accessories
1.1.1 Marking
1.1.1.1 Marking device



[Item No.: 258-5000](#)
Thermal transfer printer; Smart Printer; for complete control cabinet marking; 300 dpi; With marking material