



Color: white

Technical data	
Marking method	Thermal transfer
Marking	plain
Marking differentiation	Divided into two fields
Delivery form	Roll
Delivery form configuration	750 labels/reel; 1 line
Printing device	Smart Printer (thermal transfer printer)

Physical data	
Depth	0.06 mm

Mechanical data	
Mounting type	Sticking
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Material data	
Color	white
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	Acrylic; permanent
Halogen-free	Yes
Weight	600 g
Fire load	0 MJ



Environmental requirements	
Ambient temperature (storage)	+10 ... +21 °C
Ambient temperature (operation)	-40 ... +150 °C
Relative humidity	40 ... 50 %

Commercial data	
eCl@ss 10.0	27-40-06-29
eCl@ss 9.0	27-40-06-29
ETIM 9.0	EC001288
ETIM 8.0	EC001288
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143456067
Customs tariff number	39199080888

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 210-813

↓

Documentation			
Bid Text		Operating Instructions	
210-813	19.02.2019	xml 2.62 KB	↓
210-813	09.01.2019	docx 14.47 KB	↓
		210-813 Information on handling print material	1 28.08.2020 pdf 1353.96 KB ↓

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marking device



Item No.: 258-5000

Thermal transfer printer; Smart Printer; for complete control cabinet marking; 300 dpi; With marking material

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com