

RANA LED Surface 1500
RANA LED S 1500 LO 4K LOUV+PRI W GEN2
0051505



PRODUCT OVERVIEW

Product name	RANA LED S 1500 LO 4K LOUV+PRI W GEN2
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
E-number FI	4273704
Warranty	5 years
Fixture luminous flux (lm)	4000
Luminaire efficacy (lm/W)	118
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	34
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	White
IP rating	IP20
IK rating	IK07
Product EAN number	5410288515052

DATA TABLE

General data	
Product name	RANA LED S 1500 LO 4K LOUV+PRI W GEN2
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended

RANA LED Surface 1500

RANA LED S 1500 LO 4K LOUV+PRI W GEN2

0051505

Performance ambient temperature Tq (°C) 25

E-number FI 4273704

Warranty 5 years

Optical data

Fixture luminous flux (lm) 4000

Luminaire efficacy (lm/W) 118

Colour temperature (K) 4000

Light colour Neutral White

CRI (Ra) 80

Colour Variation Initial (SDCM) SDCM3

Glare control < 19

Photobiological Risk Group RG0

Electrical data

Total power consumption (W) 34

Primary Supply/Product voltage - min (V) 220

Lamp power factor 0.95

Electrical protection Class I

Control gear type LED driver constant current

Drive current (mA) 275

Inrush Current (A) 25

Inrush Duration (µs) 280

Glow Wire Test (°C) 850

Energy Efficiency Class (A->G) of contained light source C, C(more than 1 Light Source)

Nominal Frequency (Hz) 50/60Hz

Max. products per 10A C Breaker 23

Max. products per 20A B Breaker 30

Connectable conductor cross section - Min (mm²) 2.5

Connectable conductor cross section - Max (mm²) 2.5

Lifetime data

Lifespan L70 B50 50000

Lifespan L70 B10 50000

Lifespan L80 B50 50000

Lifespan L80 B10 50000

Lifespan L90 B50 50000

Lifespan L90 B10 50000

Physical data

Housing colour White

IP rating IP20

IK rating IK07

Diffuser finish Prismatic


Diffuser material PC Polycarbonate

Nominal Product Length (mm) 1460

RANA LED Surface 1500
RANA LED S 1500 LO 4K LOUV+PRI W GEN2
0051505

Nominal Product Width (mm)	187
Weight (kg)	4.2
Packaging	
Single packaging type	Carton
Product EAN number	5410288515052
Packaging single width (cm)	6.5
Packaging single depth (cm)	21.0
DUN14 (outer)	05410288515052
Packaging outer length / height (cm)	153.5

PHOTOMETRY



TECHNICAL DRAWINGS

