

Surface-mounting external unit 16 mm with 1 illuminated touch button

This compact surface-mounting unit in aluminium has a surface-mounting height of only 16 mm. The external unit is equipped with a 5 mm-thick name plate in Plexiglas which is vandal proof. The metal-plated push-button contacts are maintenance-free and durable. This external unit works with 2-wire technology, which means that an existing bell can simply be replaced by this external unit. This external unit has 1 illuminated touch button.

Technical data

Surface-mounting external unit 16 mm with 1 illuminated touch button.

- Function:
 - each non-programmed push button can operate the light, light symbol supplied
 - Acknowledgement tone when pressing the bell button
 - material push buttons: metal with gilded, maintenance-free contacts
 - long-life energy-saving name plate lighting
 - 5 mm thick, indestructible and vandal proof name place in Plexiglass
 - internal memory for the exchange of data between identical external units (EEPROM)
- Mounting method: surface mounting
- Dimensions info field: 53 x 62 mm (HxW)
- Microphone: volume and microphone sensitivity can be adjusted manually
- With camera: false
- Extra terminal:
 - R-terminal to connect an extended function (e.g. door release)
 - door opener time on R-terminal: 3 s (can be adjusted via service unit)
 - activation time of the door relay (for controlling the memory in internal units): 56 s (can be adjusted via service unit).
 - speech connection during activation of the door relay (can be adjusted via service unit)
 - length of conversation: 56 s (can be adjusted via service unit)
- Input current standby: $I(a) = 0.4 \text{ mA}$, $I(P) = 11 \text{ mA}$
- Input current: 21 mA
- Material finishing: aluminium
- Colour: grey
- Marking: CE

