

Product data sheet

Item No. 94.425.5004.7

Cable assembly BST14I2KF-S 50 50GN01

geis® Connection cable male - free end; length: 5m; type BST14I2; 2-pole; 50 V / 3 A; colour of coding: grün with black strain-relief; cable: FB-2Y(ST)Y2x2x0,8, colour: grün



Item No.	94.425.5004.7
EAN	4015573459786
Order Unit	20 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	3 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	2
Mechanical coding	Yes
Interlockable	No
Color of coding/ contact carrier	Green
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	2
Nominal cross section conductor	0.5 mm ²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	21 mm
Preparation of conductor ends	Other
Cable type	FB-2Y(ST)Y 2x2x0.8



Cable colour	Green
Cable diameter	6.1 mm
Version of cable	Male - free end

Material

Surface finish	Gilt
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	5 m
--------------	-----

Technical drawing

.F	Steckereinsatz plug insert	Kabel / cable	Codierung *X*
.7	Farbe: grün colour: green	Farbe: grün colour: green	
.9	Farbe: pastellblau colour: pastel blue	Farbe: grau colour: grey	

Der weiße und gelbe Leiter sowie der Beilaufdraht ist um 21 mm gekürzt.
The white and yellow conductor as well as the filter wire will be shorted about 21mm

2 (-) = schwarz/black
1 (+) = rot/red

Teile-Nr. part-no.	L	Beispiel (Farbe: grün) example (colour: green)	Typ type
94.425.XX04.F	XX in dm-Schritten	94.425.1004.7 = 10dm/L= 1000mm	BST1412KF-S 50 10GN01
U4.425.XX04.F	XX in m-Schritten	U4.425.1204.7 = 12 m/L=12000mm	BST1412KF-S 50 X12GN01

Typ/type: BST1412KF-S 50
GN01 = grün / green
PB02 = pastellblau / pastel blue

Weitere Daten siehe Katalog further data see catalog

Erstellung / Creation	2005	Tag/Date	Name	Zeichnung Nr./Drawing No.	Index
Gezeichnet / Drawn	24.05.	Schnitt / Section		94.425.0204.7 01K	a
Geprüft / Checked					
Freigegeben / Released					

Wieland Elektrische Werkbroschungen

KONFEKT_LEITUNG
Niedervolt 50V - 3A 0,5 qmm Stecker-freies Ende
connection lead male-free end