



# Product data sheet Spirotech

## ETIM product data

|   |                        |
|---|------------------------|
| Housing material                          | Steel                  |
| With drain valve                          | No                     |
| Housing material quality                  | St 37 (1.0254)         |
| Backwash filter                           | No                     |
| Medium temperature (continuous)           | 0 - 110 °C             |
| Max. operating pressure                   | 10 bar                 |
| KVS value [m <sup>3</sup> /h] at ΔP 1 bar | 73.1 m <sup>3</sup> /h |
| Variable flow direction                   | Yes                    |
| With insulation                           | No                     |
| Separator type                            | Air                    |
| Connection                                | Flange                 |
| Model                                     | Horizontal             |
| Nominal diameter                          | DN 50                  |
| Max. glycol mixture                       | 50 %                   |
| Suitable for heating                      | Yes                    |
| Suitable for cooling                      | Yes                    |

|                              |                          |
|------------------------------|--------------------------|
| Construction length          | 350 mm                   |
| Article compression class    | PN 10                    |
| Surface protection           | Lacquered                |
| Suitable for open system     | No                       |
| Suitable for closed system   | Yes                      |
| Suitable for solar           | No                       |
| With dismountable filter     | No                       |
| Filter volume                | 7 l                      |
| Magnet operating principle   | No                       |
| With automatic de-aerator    | Yes                      |
| With couplers                | No                       |
| Inlet/outlet offset distance | 0 mm                     |
| Material of connection       | Steel                    |
| Flow-through capacity        | 0 - 25 m <sup>3</sup> /h |
| Flange standard              | DIN                      |

### Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website

