

## 19PKW-2005: Press fitting with Eurocone coupling 20x3/4'



### Commercial information

PVDF press fittings in combination with multilayer pipe, a completely corrosion-free system. The synthetic press fittings are made from injection moulded PVDF (Polyvinylidene fluoride)\*. PVDF offers the user a unique combination of properties:

- Highly resistant to pressure and temperature
- Excellent mechanical strength
- Extreme flexibility: bending up to 10° is possible
- Perfectly suited for drinking water and food
- Highly resistant to chemicals and corrosion
- Embedding is possible without extra protection

#### Basic unit dimensions

Height	33 mm
Length	58 mm
Width	33 mm
Net weight	0.035 kg

#### Certificates

QB (CSTBat), ATG, ETA, SINTEF, STF, AFNOR, ACS, RISE, DVGW Wasser, Aenor, Sans 21003

#### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material	Plastic	Bend radius	0 Millimetre
Material connection 1	Polyvinylidene fluoride (PVDF)	Outer pipe diameter connection 1	20 Millimetre
Material quality	Polyvinylidene fluoride (PVDF)	Wall thickness, connection 1	0.7 Millimetre
Material quality connection 1	Polyvinylidene fluoride (PVDF) (expired)	Length	58 Millimetre
Surface protection connection 1	Untreated	Length of connection 1	31 Millimetre
Surface treatment connection 1	Untreated	Working length connection 1	4 Millimetre
Material connection 2	Polyvinylidene fluoride (PVDF)	Length of connection 2	27 Millimetre
Material quality connection 2	Polyvinylidene fluoride (PVDF) (expired)	Working length connection 2	12 Millimetre
Surface protection connection 2	Untreated	Wrench width	0 Millimetre
Surface treatment connection 2	Untreated	Wrench width union nut	0 Millimetre
Shape	Straight	Medium temperature (continuous)	-10 70 Degrees celsius
Reducing	✘	Max. operating pressure at 20 °C	16 Bar
Eccentric	✘	Standard Dimension Ratio (SDR)	0
System specific	✓		
Connection 1	Press sleeve		
Contour code connection 1	TH/BE		
Nominal diameter connection 2	3/4 inch (20)		
Main colour fitting	White		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
KIWA certified	✘		
Gastec QA mark	✘		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		