

169-276 3500K 60 degree specific configuration
Track spot | black | spot | 8W | 930-935-940 | 45° | dim.

Introduction

Purpose of this Document

This document provides information for 169-276 3500K 60 degree. During measurement, the product is used in a different mode where output power, colour temperature and/or beam angle are changed from factory standard. These adjustments can be made without altering the product and are designed to be set by the installer. In most cases, the options are set through switches on the product.

Results

Total input power	8.1 W
Correlated Colour Temperature	3427 K
Total lumen output	560 lm
Efficiency	69 lm/W


Electrical measurement details

Input Power

RMS Input voltage feed. V_{RMS}	235 V
RMS Input current feed. I_{RMS}	0.036 A
Total input power	8.1 W
Frequency of input power	50.1 Hz
Power factor	0.96
Displacement power factor	0.98
Total harmonic distortion of the current	21.18%
Total harmonic distortion of the voltage	2.74%

Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 24.2%




Lumen efficiency: 69 lm/W



Harmonics

3rd Harmonic	17.7%
5th Harmonic	8.01%
7th Harmonic	5.07%
9th Harmonic	2.42%
11th Harmonic	2.41%

Current Harmonics %




169-276 3500K 60 degree specific configuration

Colour measurement details



Total lumen output 560 lm
 Correlated Colour Temperature 3427 K
 Colour coordinates CIE 1931 (x;y) = (0.404;0.379)
 Colour deviation from BBL Duv = -0.0051

TM30-18 Colour Fidelity Index R_f 91.4
 TM30-18 Colour Gamut Index R_g 100.0
 Colour Rendering Index (Ra) CRI 94.6
 Colour Rendering Index. (red component) $R_9 = 70.0$


Colour Quality Scale CQS = 92.1
 Television Lighting Consistency Index TLCI = 93




Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	91	-4%	1%
C2	93	-2%	3%
C3	91	0%	4%
C4	94	-1%	1%
C5	93	-3%	1%
C6	96	1%	0%
C7	94	-3%	1%
C8	97	-1%	1%
C9	92	-1%	5%
C10	88	0%	8%
C11	86	3%	8%
C12	90	7%	1%
C13	92	3%	-5%
C14	88	5%	-8%
C15	89	0%	-6%
C16	88	-1%	-7%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale