


30P-1615S-2: Press adapter to copper compression 16x15



Commercial information

Dit overgangsstuk is ideaal om van een bestaande installatie uit koper snel en gemakkelijk over te schakelen naar het Henco meerlagenbuis systeem. Systeem is aan te sluiten met een knelkoppeling en te connecteren op het meerlagenbuis met een persfitting.

Certificates

QB (CSTBat), KIWA, KOMO, DVGW Wasser, ATG, ÖN EN 21003-2/-3, ÖVGW Wasser, ETA, STF, AFNOR, ACS, WRAS, GOST-R, PZH, ITC, TSU, DNV-GL, Sans 21003, Kontrol Biro, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary


Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

| | | | |
|------------------------------------|--|----------------------------------|------------------------|
| Material connection 1 | Brass | Bend radius | 0 Millimetre |
| Material quality connection 1 | CuZn40Pb2 (CW617N) | Outer pipe diameter connection 1 | 16 Millimetre |
| Surface protection connection 1 | Untreated | Outer pipe diameter connection 2 | 15 Millimetre |
| Surface treatment connection 1 | Untreated | Length | 61 Millimetre |
| Material connection 2 | Brass | Length of connection 1 | 35.5 Millimetre |
| Material quality connection 2 | CuZn40Pb2 (CW617N) | Working length connection 1 | 35.5 Millimetre |
| Surface protection connection 2 | Untreated | Length of connection 2 | 16.5 Millimetre |
| Surface treatment connection 2 | Untreated | Working length connection 2 | 10.5 Millimetre |
| Shape | Straight | Wrench width | 0 Millimetre |
| Reducing | ✘ | Wrench width union nut | 0 Millimetre |
| Eccentric | ✘ | Medium temperature (continuous) | -10 70 Degrees celsius |
| System specific | ✓ | Max. operating pressure at 20 °C | 16 Bar |
| Connection 1 | Press sleeve | Standard Dimension Ratio (SDR) | 0 |
| Contour code connection 1 | TH | | |
| Connection 2 | Clamp connection | | |
| Material sealing | Ethylene-propylene diene monomer rubber (EPDM) | | |
| With buffer stud | ✓ | | |
| High tensile strength | ✘ | | |
| With thermal insulation | ✘ | | |
| Ring stiffness class | Other | | |
| With sealing rings/gaskets | ✓ | | |
| Capped | ✘ | | |
| With drain valve | ✘ | | |
| With de-aerator | ✘ | | |
| FM quality mark | ✘ | | |
| LPCB quality mark | ✘ | | |
| ULC quality mark | ✘ | | |
| UL quality mark | ✘ | | |
| DIN-CERTCO certificate | ✘ | | |
| VdS quality mark | ✘ | | |
| With approval for TÜV | ✘ | | |
| DVGW quality mark for gas | ✘ | | |
| DVGW quality mark for water | ✓ | | |
| KIWA certified | ✓ | | |
| Gastec QA mark | ✘ | | |
| KOMO certified | ✓ | | |
| Type approval according to BBR/EKS | ✘ | | |

Related products

| Product code | GTIN | Description | Image |
|--------------|----------------|---|---|
| BE16MINI3 | 05414764328211 | Henco Jaw for press machine M-BMINI3 BE/TH-Profile 16mm |  |

