

169-362 4000K 60 degree specific configuration
Track spot | 3-phase | black | 30W | 930-935-940 | 45° | dim

Introduction

Purpose of this Document

This document provides information for 169-362 4000K 60 degree. During measurement, the product is used in a different mode where output power, colour temperature and/or beam angle are changed from factory standard. These adjustments can be made without altering the product and are designed to be set by the installer. In most cases, the options are set through switches on the product.

Results

Total input power	29.1 W
Correlated Colour Temperature	3919 K
Total lumen output	2350 lm
Efficiency	81 lm/W

Electrical measurement details

Input Power


RMS Input voltage feed. V_{RMS}	231 V
RMS Input current feed. I_{RMS}	0.131 A
Total input power	29.1 W

Frequency of input power	49.9 Hz
Power factor	0.96
Displacement power factor	0.97

Total harmonic distortion of the current	17.13%
Total harmonic distortion of the voltage	2.41%

Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 24.7%




Lumen efficiency: 81 lm/W



Harmonics

3rd Harmonic	14.58%
5th Harmonic	5.56%
7th Harmonic	2.99%
9th Harmonic	4.19%
11th Harmonic	1.82%

Current Harmonics %




169-362 4000K 60 degree specific configuration

Colour measurement details


Total lumen output 2350 lm
 Correlated Colour Temperature 3919 K
 Colour coordinates CIE 1931 (x;y) = (0.382;0.370)
 Colour deviation from BBL Duv = -0.0034

TM30-18 Colour Fidelity Index R_f 90.2
 TM30-18 Colour Gamut Index R_g 101.9
 Colour Rendering Index (Ra) CRI 94.0
 Colour Rendering Index. (red component) $R_9 = 74.9$


Colour Quality Scale CQS = 91.0
 Television Lighting Consistency Index TLCI = 86



Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	92	-4%	-1%
C2	95	-2%	2%
C3	88	-1%	6%
C4	91	0%	5%
C5	91	2%	4%
C6	93	5%	1%
C7	96	1%	-1%
C8	95	-1%	0%
C9	94	-2%	3%
C10	87	-3%	7%
C11	83	2%	11%
C12	86	6%	4%
C13	89	6%	-4%
C14	91	9%	1%
C15	89	3%	-7%
C16	87	0%	-8%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale