


## 30PG-2022S: Press adapter to copper compression Gas 20x22



### Commercial information

Deze fittingen bieden grote voordelen ten aanzien van corrosie. De fittingen zijn voorzien van een speciale O-ring, Deze O-ring is gemaakt van het materiaal HNBR en is bestand tegen gas.

Het huis van de fitting bestaat uit messing CW617N.

De fitting is voorzien van een stotingring om direct galvanisch contact tussen het aluminium van de buis en het messing van de fitting te voorkomen.

Elektrolyse is hierdoor uitgesloten.

De fitting is uitgerust met O-ringen uit EPDM en RVS pershulzen met 3 controlevensters.

Om montagefouten te voorkomen zijn de RVS pershulzen voorzien van de maatvoering en het type persprofiel waarmee geperst kan worden.

#### Certificates

DVGW Gas, GASTEC

#### Applications

Gas

#### Solutions

Building installations, Industry, Oil & gas, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Outer pipe diameter connection 1	20 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 2	22 Millimetre
Surface treatment connection 1	Untreated	Length	61 Millimetre
Material connection 2	Brass	Length of connection 1	36 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Working length connection 1	36 Millimetre
Surface protection connection 2	Untreated	Length of connection 2	17 Millimetre
Surface treatment connection 2	Untreated	Working length connection 2	17 Millimetre
Shape	Straight	Wrench width	0 Millimetre
Reducing	✓	Wrench width union nut	0 Millimetre
Eccentric	✗	Medium temperature (continuous)	-20 60 Degrees celsius
System specific	✓	Max. operating pressure at 20 °C	16 Bar
Connection 1	Press sleeve	Standard Dimension Ratio (SDR)	0
Contour code connection 1	TH		
Connection 2	Clamp connection		
Material sealing	Hydrogenated acrylonitrile butadiene rubber (HNBR)		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✓		
DVGW quality mark for water	✗		
KIWA certified	✗		
Gastec QA mark	✓		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		

## Related products