

## Han 3HvE-gg-M25



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 34 003 0421                                                                        |
| Specification      | Han 3HvE-gg-M25                                                                       |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19340030421">https://b2b.harting.com/19340030421</a> |

### Identification

|                          |                  |
|--------------------------|------------------|
| Category                 | Hoods/Housings   |
| Series of hoods/housings | Han Hv E®        |
| Type of hood/housing     | Hood             |
| Type                     | Low construction |

### Version

|                      |                                                     |
|----------------------|-----------------------------------------------------|
| Size                 | 10 B                                                |
| Version              | Top entry                                           |
| Cable entry          | 1x M25                                              |
| Locking type         | Double locking lever                                |
| Field of application | Special hoods/housings for Han Hv E® screw terminal |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65            |
| Type rating acc. to UL 50 / UL 50E     | 4               |
|                                        | 4X              |
|                                        | 12              |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast   |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 7037 (dust grey) |
| RoHS                    | compliant            |



Pushing Performance

## Material properties

|                             |               |
|-----------------------------|---------------|
| ELV status                  | compliant     |
| China RoHS                  | e             |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances  | Not contained |
| REACH SVHC substances       | Not contained |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
| CE        | Yes    |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 118.4 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |