



Color: white

Technical data	
Marking method	Thermal transfer
Marking	plain
Marking differentiation	Divided into three fields
Delivery form	Roll
Delivery form configuration	750 labels/reel; 1 line
Printing device	Smart Printer (thermal transfer printer)

Physical data	
Depth	0.06 mm

Mechanical data	
Mounting type	Sticking
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Material data	
Color	white
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	Acrylic; permanent
Halogen-free	Yes
Weight	244.8 g
Fire load	0 MJ



Environmental requirements		
Ambient temperature (storage)		+10 ... +21 °C
Ambient temperature (operation)		-40 ... +150 °C
Relative humidity		40 ... 50 %

Commercial data		
eCl@ss 10.0		27-40-06-29
eCl@ss 9.0		27-40-06-29
ETIM 9.0		EC001288
ETIM 8.0		EC001288
PU (SPU)		1 pcs
Packaging type		Box
Country of origin		DE
GTIN		4055143641753
Customs tariff number		39199080888

Environmental Product Compliance		
RoHS Compliance Status		Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 210-814	

Documentation

Bid Text			
210-814	19.02.2019	xml 2.61 KB	
210-814	08.01.2019	docx 14.55 KB	

Operating Instructions			
210-813 Information on handling print material	1 28.08.2020	pdf 1353.96 KB	

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marking device



Item No.: 258-5000
Thermal transfer printer; Smart Printer; for complete control cabinet marking; 300 dpi; With marking material