

Product data sheet

Item No. 96.021.0053.0

Female connector with strain relief RST20i2F B23ZR1 GL

Connector RST20i2, 2 pole, female, spring clamp connection, 250V/20A, for cable diameters 6-10 mm, color of coding: light gray, color of housing: light gray



Item No.	96.021.0053.0
EAN	4015573890282
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	

Connection Data

Cable diameter	6 mm
Connection cross section solid	2.5 mm ²
Connection cross section stranded	1.5 mm ²
Terminations per pole	2

Model

Model	female
-------	--------

Number of poles	2
Connection type	Tension clamp connection
Degree of protection (IP)	IP66/IP68
Remark to type of connection	Finely stranded con. req. Wieland cable end sleeve

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	80.4 mm
Width	34.6 mm
Height	34.6 mm

Technical drawing

