



Features

• Surface or Suspended LED Linear luminaire with Louvre + Prismatic Optic, Direct Light Distribution, Luminaire Dimensions: 616x616x47mm, Sylvania White body colour, IP20, IK07, Electric Class 1, Light Engine Dimensions: 570x65+570x65mm, SylSmart (SSC01) controlled, Low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 3000lm, 29W, 103lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<19, Luminance at 65° < 3000 cd/m2, Lumen Maintenance: L90B10 at 50,000 hours, Quick electrical connection with push-connectors in the luminaire, Glow Wire Test 850°C.


Product Overview

Product name	RANA LED S 600 LO 4K LOUV+PRI SSC W GEN2
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Fixture luminous flux (lm)	3000
Luminaire efficacy (lm/W)	103
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	29
Electrical protection	Class I
Control gear type	Electronic ballast
Housing colour	White
IP rating	IP20
IK rating	IK07

RANA LED S 600 LO 4K LOUV+PRI SSC W GEN2
0051857

Product EAN number	5410288518572
Warranty	5 years

Photometry



Technical drawings

