


Data Sheet | Item Number: 787-2801

DC/DC Converter; 24 VDC input voltage; 5 VDC output voltage; 0.5 A output current; DC OK contact

<https://www.wago.com/787-2801>



DC O.K.	1		5	n.c.
GND	2		6	n.c.
Vout+	3		7	Vin+
GND	4	OUT	IN	8



Dimensions in mm

Features:

- DC/DC converter in a compact 6 mm housing
- DC/DC converters (787-28xx) supply devices with 5, 10, 12 or 24 VDC from a 24 or 48 VDC power supply with an output power up to 12 W.
- Output voltage monitoring via DC OK signal output
- Can be commoned with 857 and 2857 Series devices
- Comprehensive range of approvals for multiple applications

Technical data

Input	
Nominal input voltage $U_{i, nom}$	DC 24 V
Input voltage range	DC 10 ... 30 V
Nominal mains frequency range	0 Hz
Input current I_i	≤ 0.34 A
Inrush current	≤ 0.5 A (at nominal input voltage)

Output	
Nominal output voltage $U_{o, nom}$	DC 5 V
Output voltage range	± 3 %
Nominal output current $I_{o, nom}$	0.5 A
Nominal output power	2.5 W
Deviation	≤ 3 %
Load regulation	≤ 1 %
Residual ripple	≤ 20 mV (peak-to-peak)

Signaling and communication

Signaling	1 x LED DC OK (green) 1 x Short circuit LED (red) 1 x Active signal output (U_r , max. 4 mA)
Operation status indicator	Green LED (U_o) Red LED (short circuit)

Efficiency/power losses

Power loss P_I	≤ 0.13 W; ≤ 0.6 W (nominal load)
Efficiency (typ.)	82.5 % (at nominal input voltage and nominal output)

Circuit protection

Internal fuse	No
---------------	----

Safety and protection

Protection class	III
Protection type	IP20; per EN 60529
Reverse voltage protection	Yes
Resistance to reverse feed	\leq DC 16 V
Pollution degree	2
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	No
Series operation	No
MTBF	$> 1,800,000$ h

Connection data

Number of jumper slots	8
Connection technology	Push-in CAGE CLAMP®
WAGO connector	WAGO 857 Series
Solid conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Fine-stranded conductor	0.34 ... 2.5 mm ² / 22 ... 14 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 inches

Physical data

Width	6 mm / 0.236 inches
Height	94 mm / 3.701 inches
Depth from upper-edge of DIN-rail	97.8 mm / 3.85 inches

Mechanical data

Mounting type	DIN-35 rail
---------------	-------------

Material data

Fire load	0.418 MJ
Weight	48.6 g

Environmental requirements

Ambient temperature (operation)	-25 ... +70 °C
Ambient temperature (storage)	-40 ... +85 °C
Relative humidity	≤ 95% (no condensation permissible)
Derating	No derating
Climatic category	3K3 (per EN 60721; except for low air pressure)

Standards and specifications

Conformity marking	CE
Standards/specifications	EN 61000-6-2 EN 61000-6-3 EN 60950-1 UL 61010-2-201

Commercial data

eCl@ss 10.0	27-04-07-01
eCl@ss 9.0	27-04-07-01
ETIM 8.0	EC002540
ETIM 7.0	EC002540
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4055143407052
Customs tariff number	85044083900

Environmental Product Compliance

CAS-No.	11120-22-2 1303-86-2 1317-36-8 7439-92-1
REACH Candidate List Substance	Diboron trioxide Lead Lead monoxide Lead silicate
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	dd50b732-8f7f-4611-b548-bf9573ea47e5
SCIP notification number (Belgium)	ac3172f8-3cbe-4f5b-9673-cd53b2ff89b8
SCIP notification number (Bulgaria)	21260fb1-503b-4168-9dba-d4525e9688c5
SCIP notification number (Czech Republic)	fa0beb31-1f2e-4c70-9a5a-b2bf14d31c85
SCIP notification number (Denmark)	0ad7bafd-8a3f-4226-bcf8-90ccd0e1b480
SCIP notification number (Finland)	322b3f8e-3e92-42ca-b31b-ff2e12ae260b
SCIP notification number (France)	1716346b-8c81-4e60-ae92-991ce8df89bd
SCIP notification number (Germany)	c45cc0ab-24fa-4039-8544-5e118629f44a
SCIP notification number (Hungary)	2b916107-02f4-4a9e-abad-02090b60a02c
SCIP notification number (Italy)	399b6ded-51df-4a3d-a176-1a41fd98f76b
SCIP notification number (Netherlands)	65de8cba-9fda-4434-a0b1-d526e9af032b
SCIP notification number (Poland)	0bc56092-a29d-4805-9a94-5c8dd1a2a9fd
SCIP notification number (Romania)	cae1bd68-4828-4698-9fb8-cc38c4553b4d
SCIP notification number (Sweden)	1a0a3f03-4fbd-4318-be50-926c4dfdba0f

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
EAC Brjansker Zertifizierungsstelle	TP TC 020/2011	EAC_Certificate_RU_C-DE.AM02.B.00115_19
UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199 Vol3 Sec1

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
----------	----------	------------------

EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
--	---	---

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 787-2801



Documentation

Bid Text

787-2801	19.02.2019	xml 5.65 KB	
787-2801	11.01.2016	doc 34.00 KB	
787-2801	11.01.2016	docx 19.85 KB	
787-2801	11.01.2016	pdf 89.66 KB	

Instruction Leaflet

DC/DC-Wandler	V 1.1.1 31.03.2020	pdf 2359.41 KB	
---------------	-----------------------	-------------------	--

CAD/CAE-Data

CAD data

2D/3D Models 787-2801	
--------------------------	--

CAE data

EPLAN Data Portal 787-2801	
WSCAD Universe 787-2801	
ZUKEN Portal 787-2801	

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marker



Item No.: 793-5501

WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white

Item No.: 793-502

WMB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-566

WMB marking card; as card; MARKED; 1 ... 50 (2x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-503

WMB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-504

WMB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-505

WMB marking card; as card; MARKED; 31 ... 40 (10x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-506

WMB marking card; as card; MARKED; 41 ... 50 (10x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-501

WMB marking card; as card; not stretchable; plain; snap-on type; white



Item No.: 2009-115

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

1.1.1.2 Marking strip



Item No.: 2009-110

Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

1.1.2 Tool

1.1.2.1 Operating tool



Item No.: 210-720

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured