



Color: ■ orange

Material data

Color	orange
Insulation material (main housing)	Polycarbonate (PC)
Flammability class per UL94	V2
Fire load	0.015 MJ
Weight	0.5 g

Commercial data

Product Group	26 (picoMAX Connectors)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821479260
Customs tariff number	82055980000

Product Classification

UNSPSC	27112109
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status

Compliant, No Exemption

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc.	UL 1977	E45171

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 2092-1630



CAD/CAE-Data

CAD data

2D/3D Models
2092-1630




CAE data

ZUKEN Portal
2092-1630




Installation Notes


Locking system



Disconnecting female connector via unlocking tool. Plug unlocking tool into the male header's locking latch.



Disconnecting a female connector via unlocking tool. Plug unlocking tool into the male header's locking latch.



Pull on both unlocking tool and conductors to remove female connector from male header.