




Omschrijving Bandella flessibile
Nominale stroom 250 A

CONDUCTOR CHARACTERISTICS		INSULATING CHARACTERISTICS	
Materiaal	Rame elettrolitico stagnato (Cu-ETP)	Elongation	500%
Layers number (N)	3	Bedrijfstemperatuur	-50°C +115°C
Base	20 mm (A)	Insulation thickness	1,8 mm
Single layer height	1 mm (B)	Self-extinguishing (UL 94)	V0
Sectie (mm ²)	60	Self-extinguishing (IEC 60695-2-11)	960°C (GWT)
Current coefficient of two busbars in parallel	1,72	Nominale spanning	1000 Vac - 1500 Vdc
Current coefficient of three busbars in parallel	2,25	Dielectric strenght	20 kV/mm
RANGE	-	-	-
ΔT 20K	228 A	-	-
ΔT 30K	280 A	-	-
ΔT 40K	323 A	-	-
ΔT 50K	360 A	-	-
ΔT 60K	395 A	-	-
ΔT 70K	428 A	-	-

DIMENSIONAL





Product Data Sheet

GW47652

BUSBAR-serie

STANDARDS/APPROVALS



GEWISS S.p.A. Via Domenico Bosatelli 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 10/03/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice