




Omschrijving Bandella flessibile  
Nominale stroom 400 A

CONDUCTOR CHARACTERISTICS		INSULATING CHARACTERISTICS	
Materiaal	Rame elettrolitico stagnato (Cu-ETP)	Elongation	500%
Layers number (N)	5	Bedrijfstemperatuur	-50°C +115°C
Base	20 mm (A)	Insulation thickness	1,8 mm
Single layer height	1 mm (B)	Self-extinguishing (UL 94)	V0
Sectie (mm <sup>2</sup> )	100	Self-extinguishing (IEC 60695-2-11)	960°C (GWT)
Current coefficient of two busbars in parallel	1,72	Nominale spanning	1000 Vac - 1500 Vdc
Current coefficient of three busbars in parallel	2,25	Dielectric strenght	20 kV/mm
<b>RANGE</b>	-	-	-
ΔT 20K	228 A	-	-
ΔT 30K	326 A	-	-
ΔT 40K	376 A	-	-
ΔT 50K	420 A	-	-
ΔT 60K	460 A	-	-
ΔT 70K	498 A	-	-

### DIMENSIONAL





Product Data Sheet

**GW47653**

BUSBAR-serie

STANDARDS/APPROVALS



GEWISS S.p.A. Via Domenico Bosatelli 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

[www.gewiss.com](http://www.gewiss.com)  
[sat@gewiss.com](mailto:sat@gewiss.com)  
Last update 10/03/2026

Data, measures, designs and pictures are shown  
only as informative purposes,  
and could be changed without previous notice