

36P-1612P: Press adapter to copper press 16x12 cusi



Commercial information

- Press-fit adapter (M,V & SA Profile)
- Quick and more reliable solution than compression fittings
- M, V & SA-profile can be used on copper side.
- Can be used in concrete if the fitting is protected
- Can be used in spaces which are difficult to reach
- Brass CW724 "CuSi"
- Compatible with thin-walled steel, copper, stainless steel

Certificates

QB (CSTBat), DVGW Wasser, SINTEF, KIWA, KOMO, ATG, ÖN EN 21003-2/-3, ÖVGW Wasser, ETA, STF, AFNOR, ACS, WRAS, GOST-R, PZH, ITC, TSU, DNV-GL, RISE, Sans 21003, Kontrol Biro, EMI

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	16 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	12 Millimetre
Material connection 2	Brass	Length	54 Millimetre
Surface protection connection 2	Untreated	Length of connection 1	26 Millimetre
Surface treatment connection 2	Untreated	Working length connection 1	20 Millimetre
Shape	Straight	Length of connection 2	25 Millimetre
Reducing	✘	Working length connection 2	19.5 Millimetre
Eccentric	✘	Wrench width	0 Millimetre
System specific	✓	Wrench width union nut	0 Millimetre
Connection 1	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
Contour code connection 1	TH	Max. operating pressure at 20 °C	16 Bar
Connection 2	Press sleeve	Standard Dimension Ratio (SDR)	0
Contour code connection 2	M/F (seal) (expired)		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		

Related products

Product code	GTIN	Description	Image
BE16MINI3	05414764337824	Henco Jaw for press machine M-BMINI3 BE/TH-Profile 16mm	

