




Omschrijving Bandella flessibile
Nominale stroom 630 A

CONDUCTOR CHARACTERISTICS

Materiaal	Rame elettrolitico stagnato (Cu-ETP)	- INSULATING CHARACTERISTICS	
Layers number (N)	8	Elongation	500%
Base	24 mm (A)	Bedrijfstemperatuur	-50°C +115°C
Single layer height	1 mm (B)	Insulation thickness	1,8 mm
Sectie (mm ²)	192	Self-extinguishing (UL 94)	V0
Current coefficient of two busbars in parallel	1,72	Self-extinguishing (IEC 60695-2-11)	960°C (GWT)
Current coefficient of three busbars in parallel	2,25	Nominale spanning	1000 Vac - 1500 Vdc
		Dielectric strenght	20 kV/mm
RANGE	-	-	-
ΔT 20K	429 A	-	-
ΔT 30K	525 A	-	-
ΔT 40K	606 A	-	-
ΔT 50K	678 A	-	-
ΔT 60K	743 A	-	-
ΔT 70K	802 A	-	-

DIMENSIONAL





Product Data Sheet

GW47654

BUSBAR-serie

STANDARDS/APPROVALS



GEWISS S.p.A. Via Domenico Bosatelli 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 10/03/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice