

## Data Sheet | Item Number: 726-906

Insulation stop; 0.25 mm<sup>2</sup> "s"; 0.14 - 0.25 mm<sup>2</sup> "f-st"; 4 x 3 pieces/strip; light gray

<https://www.wago.com/726-906>



Color: ■ light gray

### Notes

Safety information

Suitable for patchboard side (side 1) of 1.5 mm<sup>2</sup> matrix patchboards (front side differs from back side)

### Connection data

#### Connection 1

Solid conductor	0.25 mm <sup>2</sup> / 22 AWG
Fine-stranded conductor	0.14 mm <sup>2</sup> / 14 AWG
Strip length	8 ... 10 mm / 0.31 ... 0.39 inches

### Material data

Note (material data)

[Information on material specifications can be found here](https://www.wago.com/us/material-specifications)

Color	light gray
Fire load	0.014 MJ
Weight	0.5 g

### Commercial data

Product Group	12 (Matrix Patch Board)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	200 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918094238
Customs tariff number	39269097900

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Downloads**

**Environmental Product Compliance**

Compliance Search

Environmental Product Compliance 726-906	↓
--	---

**Documentation**

Additional Information

Technical Section	pdf 2240.62 KB	↓
-------------------	-------------------	---

Bid Text

726-906	19.02.2019	xml 2.77 KB	↓
726-906	21.02.2019	docx 14.01 KB	↓

**CAD/CAE-Data**

CAE data

WSCAD Universe 726-906	↓
------------------------	---

**Installation Notes**

**Conductor termination**



Inserting an insulation stop into conductor entry holes of matrix patchboards.



Insulation stop is in place.