

Data Sheet | Item Number: 726-907

Insulation stop; 0.25 - 0.5 mm² "s+f-st"; 4 x 3 pieces/strip; dark gray

<https://www.wago.com/726-907>



Color: ■ dark gray

Notes

Safety information

Suitable for patchboard side (side 1) of 1.5 mm² matrix patchboards (front side differs from back side)

Connection data

Connection 1

Solid conductor	0.25 ... 0.5 mm ² / 22 ... 20 AWG
Fine-stranded conductor	0.25 ... 0.5 mm ² / 22 ... 20 AWG
Strip length	8 ... 10 mm / 0.31 ... 0.39 inches

Material data

Note (material data)

[Information on material specifications can be found here](https://www.wago.com/us/material-specifications)

Color dark gray

Material group I

Insulation material Polyamide (PA66)

Flammability class per UL94 V0

Fire load 0.02 MJ

Weight 0.6 g

Commercial data

Product Group 12 (Matrix Patch Board)

eCl@ss 10.0 27-14-11-92

eCl@ss 9.0 27-14-11-92

ETIM 8.0 EC002848

ETIM 7.0 EC002848

PU (SPU) 200 (25) pcs

Packaging type Box

Country of origin DE

GTIN 4044918094245

Customs tariff number 39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 726-907	↓
--	---

Documentation

Additional Information

Technical Section	pdf 2240.62 KB	↓
-------------------	-------------------	---

Bid Text

726-907	19.02.2019	xml 2.73 KB	↓
726-907	21.02.2019	docx 14.16 KB	↓

CAD/CAE-Data

CAE data

WSCAD Universe 726-907	↓
---------------------------	---

Installation Notes

Conductor termination



Inserting an insulation stop into conductor entry holes of matrix patchboards.



Insulation stop is in place.