



Color: ■ black

Similar to illustration

### Connection data

Number of levels	1	<b>Connection 1</b>	
		Pole number	7

### Physical data

Pin spacing	3.5 mm / 0.138 inches
Solder pin length	3.5 mm
Solder pin diameter	1 mm
Drilled hole diameter with tolerance	1.2 (+0.05) mm

### Mechanical data

Suitable	Pin spacing: 3.5 mm / 0.138 inch
----------	----------------------------------

### Plug-in connection

Contact type (pluggable connector)	Male connector/plug
Connector (connection type)	for PCB
Mating direction to the PCB	90 °

### PCB contact

PCB contact	THT
-------------	-----

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	black
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0 MJ
Weight	0.7 g

**Commercial data**

PU (SPU)	500 pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918984416
Customs tariff number	85366930000

**Product Classification**

UNSPSC	39121409
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 8.0	EC002848
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Downloads**

**Environmental Product Compliance**

Compliance Search			
Environmental Product Compliance 252-907			

**Documentation**

**Additional Information**

Technical Section	03.04.2019	pdf	2027.26 KB	
-------------------	------------	-----	------------	--

**CAD/CAE-Data**

<b>CAD data</b>		<b>PCB Design</b>	
2D/3D Models 252-907		Symbol and Footprint via SamacSys 252-907	
		Symbol and Footprint via Ultra Librarian 252-907	

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: [www.wago.com](http://www.wago.com)