

Product data sheet

Item No. 96.021.4353.1

**Female connector with strain relief RST20I2S
B13ZRX SW**

Splitter connector with RST20i2, 2 pole, double strain relief (feed through wiring), female, screw connection, 250V/20A, for cable diameters 10-14 mm, color of coding: black, color of housing: black



Item No.	96.021.4353.1
EAN	4049644011573
Order Unit	100 Piece(s)

Certificates / Approvals

Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	14 mm
Cable diameter 2	10 mm
Cable diameter 3	14 mm
Cable diameter 4	10 mm
Connection cross section solid	4 mm ²
Cross section solid 2	0.75 mm ²
Connection cross section stranded	4 mm ²
Cross section stranded 2	0.75 mm ²



Terminations per pole	1
-----------------------	---

Model

Model	female
Number of poles	2
Connection type	Screw connection
Degree of protection (IP)	IP66/IP68

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	93.9 mm
Width	59 mm
Height	38 mm

Technical drawing

Auslieferungszustand
delivery status

for cable diameter 10-14mm
für Kabeldurchm. 10-14 mm

Pol unbestückt
pole unassembled

ISO

Verpackungseinheit: je 100 Stück
Packaging unit: per 100 pcs

Teilnr. Part Nr.:	Farbe color	Type
96.021.4353.1	schwarz, öhnl. RAL 9005 black, similar to RAL 9005	RST2012S B1 ZRY SW
96.021.4353.0	lichtgrau, öhnl. RAL 7035 lightgrey, similar to RAL 7035	RST2012S B1 ZRY GL

Material	2003	Tag/Date	Name	Zeichnung Nr./Drawing No.	Stück / no of	Blatt / of
Werkstoff/Material	2003	05.06.	Schubertner	T	1	1

BUCHSENTEIL MIT DOPPELZUGENTLA

ISO 9001:2015