



PHOTOMETRIC LIGHT REPORT

**AR70 | 7 watt | 2700K |
CRI>95 | 36° | dimmable |
B15D**

Article number: 175-370



Go to the
webshop
of Tronix
Lighting



TRONIX



175-370 AR70 | 7 watt | 2700K | CRI>95 | 36° | dimmable | B15D

Introduction

Purpose of this Document

This document provides accurate and objective photometric data for Tronix Lighting item 175-370. All information is based on actual measurements taken from standard production units. No modifications were made to enhance performance results. In some cases, minor adjustments—such as temporary removal of covers, cables, or mounting features—were necessary for testing purposes. These did not influence product performance.

Test Methodology

Testing was conducted using randomly selected, unopened samples from regular inventory. All tests comply with the LM-79-19 standard, the recognized method for photometric and electrical measurements of LED and OLED luminaires. This standard, an update of IES LM-79-2008, outlines environmental test conditions, stabilization procedures, measurement methods, and approved instruments. It uses absolute photometry, meaning results directly reflect the performance of the tested product, without comparison to rated lamp standards.

Product 175-370 was tested using:

- A photogoniometer to measure luminous intensity distribution at various angles
- An integrating sphere to determine total luminous flux and colour characteristics

Compliance & Certification

Item 175-370 meets the requirements of the following EU directives. Tronix Lighting certifies that all relevant tests were executed in accordance with the applicable standards, and the CE mark is applied accordingly:

- General Product Safety – Directive 2023/988/EC
- Low Voltage Directive (LVD) – Directive 2014/35/EU
- Electromagnetic Compatibility (EMC) – Directive 2004/108/EC
- Ecodesign – Directive 2009/125/EC
- RoHS 3 – Directive 2011/65/EU + Amendment 2015/863/EU

Recycling & Sustainability

Tronix Lighting is affiliated with national recycling systems for electrical and electronic waste. The luminaire is over 90% recyclable when disposed of as electronic waste at end of life. In addition, Tronix Lighting participates in national packaging recycling schemes, ensuring full compliance with both the WEEE and packaging directives.

175-370 AR70 | 7 watt | 2700K | CRI>95 | 36° | dimmable | B15D

Laboratory and equipment

Laboratory owner and location
Gonio spectrometer system and type
Spectrometer manufacturer and model

Flicker meter manufacturer and model
Oscilloscope manufacturer and model
Power meter manufacturer and model

Power source manufacturer and model

Datalogger Manufacturer and Model

Tronix Lighting BV. Uden. The Netherlands
Viso Systems Type C. horizontal
(Gonio) Ocean Optics STS VIS
(Sphere) Admesy HERA VIS 380–780nm
Viso Systems LabFlicker
Tektronix MDO3024 oscilloscope (4 Channels. 200 MHz)
Vitretek PA900 Precision Multi-Channel Harmonic Power Analyzer
(DC) Keithley Source Measure Unit SMU-2420 3A DC Source Meter
(AC) Chroma 61601 AC Source
Omega 8-Channel Thermocouple Thermometer/Data Logger

Measurement conditions gonio spectrometer

Number of C-planes and Resolution
 γ (gamma)-Resolution
Test Distance
Room Temperature and Humidity
Input Power. Power and Displacement Factors
Frequency of Input Power
Warm-up Time and Variation

2 planes – 180°
2°
1.14 m
22°C +/- 10% – RH 50% +/- 20%
7.6 W – PF 0.98 – DPF 0.99
50 Hz
Lamp stabilized in 20 min 30 sec --4.7%

Tested light source

Manufacturer and Order Code
Product Description

Tronix Lighting – 175-370
AR70 | 7 watt | 2700K | CRI>95 | 36° | dimmable | B15D

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)
Efficiency
Energy efficiency class
Peak Intensity and Beam Angle
Correlated Colour Temperature
Colour Shift. CIE u_{uv}
Colour Rendering Index
Colour Rendering TM30-18
Television Lighting Consistency Index
Flicker

291 lm – 0.22% / 99.78%
38 lm/W
G
815 cd – 32.5°
CCT = 2718 K
Duv -0.0003
CRI 97.7
 R_f 95.1 – R_g 100.0
TLCI = 97
SVM 0.01 – PstLM 0.06

175-370 AR70 | 7 watt | 2700K | CRI>95 | 36° | dimmable | B15D

Electrical measurement details

Input Power

RMS Input voltage feed. V_{RMS}

233 V

RMS Input current feed. I_{RMS}

0.033 A

Total input power

7.6 W

Frequency of input power

50 Hz

Power factor

0.98

Displacement power factor

0.99

Total harmonic distortion of the current


5.4%

Total harmonic distortion of the voltage

2.28%

Input Power Curve

Voltage - Current



Efficiency

Radiated power efficiency: 14.5%



Lumen efficiency: 38 lm/W



Harmonics

3rd Harmonic

2.1%

5th Harmonic

1.64%

7th Harmonic

2.47%


9th Harmonic

2.35%

11th Harmonic

0.94%

Current Harmonics %



Stabilization Details

Warm-up Conditions

Stable period

15 min CCT start

2735 K

Stable change max

2.0% CCT shift

-17 K

Minimum warm-up time

15 min CCT end

2718 K

Colour temperature change during warm-up

Warm-up Results

Total warmup time

Lamp stabilized in 20 min 30 sec

Output intensity change during warm-up

Output start

305 lm

Warmup variation

-4.7% Output change

-14 lm

Output end

291 lm


175-370 AR70 | 7 watt | 2700K | CRI>95 | 36° | dimmable | B15D

Colour measurement details



Total lumen output 291 lm
 Correlated Colour Temperature 2718 K
 Colour coordinates CIE 1931 (x;y) = (0.458;0.409)
 Colour deviation from BBL Duv = -0.0003

TM30-18 Colour Fidelity Index R_f 95.1
 TM30-18 Colour Gamut Index R_g 100.0
 Colour Rendering Index (Ra) CRI 97.7
 Colour Rendering Index. (red component) $R_9 = 82.3$


Colour Quality Scale CQS = 94.8
 Television Lighting Consistency Index TLCI = 97



Relative spectral power distribution



TM30 details




TM30 Colour vectors per hue bin




TM30 Colour distortion


Hue Bin	R_f	Shifts (%)	
		Chroma	Hue
C1	95	-2%	0%
C2	97	-1%	1%
C3	97	0%	1%
C4	96	-2%	-1%
C5	96	-1%	1%
C6	97	1%	1%
C7	97	-1%	1%
C8	98	1%	1%
C9	96	0%	2%
C10	94	1%	4%
C11	94	2%	4%
C12	93	4%	-2%
C13	93	1%	-5%
C14	92	2%	-6%
C15	95	-2%	-1%
C16	91	-1%	-7%



TM30-18 R_f -values per reference colour




TM30-18 R_f -values per hue bin




TM30 Chroma shift

Colour Quality details



Colour Rendering Index



Colour Quality Scale

175-370 AR70 | 7 watt | 2700K | CRI>95 | 36° | dimmable | B15D

Flicker / temporal light artefacts details

Measurement conditions

Flicker meter type	Viso Systems LabFlicker
Flicker/TLA sample rate	20000 samples/s
Measurement time	5x 180 seconds (15 minutes) for PstLM. 1.2 sec for all other indices

Flicker indices according to Illuminating Engineering Society (IES)


Flicker frequency	99.01 Hz
Percent flicker	0.42 %
Flicker index	0

TLA indices (according IEC TR 61547-1, EN 61000-3-3 and EN 61000-4-15)


An LED luminaire is considered flicker-free if the SVM value is ≤ 0.4 and if the PstLM value is ≤ 1.0

PstLM value ($F < 80$ Hz)	0.06
SVM value ($80 < F < 2000$ Hz)	0.01


Flicker frame (one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789-2015 Lighting Flicker Risk Zones




Document revision date: 17-7-2025 Measurement serial: VFR-250710-10428-SW

175-370 AR70 | 7 watt | 2700K | CRI>95 | 36° | dimmable | B15D

Beam angle

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	291 lm
Lumen Up/Down	0.22% / 99.78%
Peak Intensity	815 cd
Beam Angle (50%)	32.5°
Beam Angle (90%)	32.5°
Beam Angle (10%)	32.5°

Cut-off Angle

Average 2.5%	71.3°
--------------	-------

Field Angle

Average 10%	57°
-------------	-----


Intensity Ratio

In 120° cone	99.0%
In 90° cone	98.3%

C planes

C000-C180
C090-C270


Linear distribution diagram - Intensity (candela) vs γ-angle



Document revision date: 17-7-2025 Measurement serial: VFR-250710-10428-SW

175-370 AR70 | 7 watt | 2700K | CRI>95 | 36° | dimmable | B15D

Beam Details



Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3.3	6.6	9.8	13.1	16.4	19.7	23	26.2	29.5	32.8	36.1	39.4	42.7	45.9	49.2	52.5	55.8	59.1	62.3	65.6	ft
815	204	91	51	33	23	17	13	10	8	7	6	5	4	4	3	3	3	2	2	lux
75.8	18.9	8.4	4.7	3	2.1	1.5	1.2	0.9	0.8	0.6	0.5	0.4	0.4	0.3	0.3	0.3	0.2	0.2	0.2	fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
815	810	808	799	774	725	643	533	421	328	256	201	157	118	87	64	45	29	19	12	cd
100%	99%	99%	98%	95%	89%	79%	65%	52%	40%	31%	25%	19%	14%	11%	8%	6%	4%	2%	1%	of 0°val

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
815	810	808	799	774	725	643	533	421	328	256	201	157	118	87	64	45	29	19	12	cd
100%	99%	99%	98%	95%	89%	79%	65%	52%	40%	31%	25%	19%	14%	11%	8%	6%	4%	2%	1%	of 0°val

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
815	810	808	799	774	725	643	533	421	328	256	201	157	118	87	64	45	29	19	12	cd
100%	99%	99%	98%	95%	89%	79%	65%	52%	40%	31%	25%	19%	14%	11%	8%	6%	4%	2%	1%	of 0°val

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
815	810	808	799	774	725	643	533	421	328	256	201	157	118	87	64	45	29	19	12	cd
100%	99%	99%	98%	95%	89%	79%	65%	52%	40%	31%	25%	19%	14%	11%	8%	6%	4%	2%	1%	of 0°val

Document revision date: 17-7-2025 Measurement serial: VFR-250710-10428-SW

175-370 AR70 | 7 watt | 2700K | CRI>95 | 36° | dimmable | B15D

Light Planning – UGR table

Uncorrected, comprehensive UGR table according to CIE 117-1995

Reflectances		70	70	50	50	30	70	70	50	50	30
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room size		Viewed Crosswise					Viewed Endwise				
H = mounting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	Y										
2H	2H	7.6	8.0	7.6	8.2	8.4	7.6	8.0	7.6	8.2	8.4
	3H	7.6	8.2	7.9	8.4	8.5	7.6	8.2	7.9	8.4	8.5
	4H	7.9	8.5	8.3	8.7	8.9	7.9	8.5	8.3	8.7	8.9
	6H	8.2	8.7	8.5	9.0	9.4	8.2	8.7	8.5	9.0	9.4
	8H	8.3	8.8	8.6	9.1	9.5	8.3	8.8	8.6	9.1	9.5
	12H	8.4	8.8	8.7	9.2	9.6	8.4	8.8	8.7	9.2	9.6
4H	2H	7.3	7.9	7.7	8.1	8.3	7.3	7.9	7.7	8.1	8.3
	3H	7.7	8.1	8.0	8.5	8.9	7.7	8.1	8.0	8.5	8.9
	4H	8.1	8.6	8.5	9.0	9.5	8.1	8.6	8.5	9.0	9.5
	6H	8.6	9.0	9.1	9.4	9.7	8.6	9.0	9.1	9.4	9.7
	8H	8.6	9.1	9.2	9.4	9.8	8.6	9.1	9.2	9.4	9.8
	12H	8.8	9.1	9.3	9.5	10.0	8.8	9.1	9.3	9.5	10.0
8H	4H	8.3	8.8	8.8	9.1	9.4	8.3	8.8	8.8	9.1	9.4
	6H	8.8	9.1	9.3	9.6	10.1	8.8	9.1	9.3	9.6	10.1
	8H	9.1	9.3	9.6	9.8	10.4	9.1	9.3	9.6	9.8	10.4
	12H	9.3	9.5	9.9	10.0	10.6	9.3	9.5	9.9	10.0	10.6
12H	4H	8.3	8.6	8.8	9.0	9.5	8.3	8.6	8.8	9.0	9.5
	6H	8.9	9.1	9.4	9.6	10.3	8.9	9.1	9.4	9.6	10.3
	8H	9.1	9.3	9.7	9.8	10.4	9.1	9.3	9.7	9.8	10.4
Variations with the observer position for the luminaire spacings. S:											
S = 1.0H		3.8 / -1.7					3.8 / -1.7				
S = 1.5H		6.2 / -1.8					6.2 / -1.8				
S = 2.0H		8.0 / -2.1					8.0 / -2.1				

Coefficients of Utilization

Ceiling reflectance	80			70			50			30			10			0		
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumen delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	110	108	112	110	108	106	106	105	103	102	101	100	99	98	97	95
2	110	106	103	100	108	105	102	99	101	99	97	98	97	95	96	94	93	91
3	106	101	97	94	104	100	96	93	97	94	92	95	92	90	93	91	89	88
4	102	96	92	89	101	95	91	88	93	90	87	91	89	86	90	87	85	84
5	99	92	88	84	97	91	87	84	90	86	83	88	85	83	87	84	82	81
6	96	89	84	81	94	88	84	80	86	83	80	85	82	79	84	81	79	78
7	92	85	81	77	91	85	80	77	83	79	77	82	79	76	81	78	76	75
8	89	82	77	74	88	81	77	74	81	77	74	80	76	73	79	76	73	72
9	87	79	75	71	86	79	74	71	78	74	71	77	73	71	76	73	71	70
10	84	76	72	69	83	76	72	69	75	71	69	75	71	69	74	71	68	67