

36PG-1615P: Press adapter to copper press Gas 16x15



Commercial information

De fittingen zijn voorzien van een speciale O-ring. Deze O-ring is gemaakt van het materiaal HNBR en is bestand tegen gas.

- Persovergang van koper naar Henco pers
- Snellere en meer zekere verwerking door persverbindingaan koperzijde in tegenstelling tot een knelverbinding.
- Koperzijde geschikt voor M --, V en SA profiel persbekken
- Toegelaten om te gebruiken op moeilijkbereikbare plaatsen
- Koppeling mag ingestort worden mits beschermend verpakt
- Legering CW724 "CuSi"
- Compatibel met dunwandig staal, koper en inox

Certificates

GASTEC, DVGW Gas

Applications

Gas

Solutions

Building installations, Industry, Oil & gas, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Outer pipe diameter connection 1	16 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 2	15 Millimetre
Surface treatment connection 1	Untreated	Length	55 Millimetre
Material connection 2	Brass	Length of connection 1	27 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Working length connection 1	21.5 Millimetre
Surface protection connection 2	Untreated	Length of connection 2	25 Millimetre
Surface treatment connection 2	Untreated	Working length connection 2	20 Millimetre
Shape	Straight	Wrench width	0 Millimetre
Reducing	✘	Wrench width union nut	0 Millimetre
Eccentric	✘	Medium temperature (continuous)	-10 60 Degrees celsius
System specific	✓	Max. operating pressure at 20 °C	10 Bar
Connection 1	Press sleeve	Standard Dimension Ratio (SDR)	0
Contour code connection 1	TH		
Connection 2	Press sleeve		
Contour code connection 2	M/F (seal) (expired)		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✓		
DVGW quality mark for water	✘		
KIWA certified	✘		
Gastec QA mark	✓		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		

Related products