

## 29P-1612-CS: Press-fitt adapter to copper pipe 16x12 CW724



This press fitting extended with a piece of copper pipe (50mm) is the perfect solution to switch from an existing installation in copper to a Henco solution with multiple connections.

### Commercial information

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 22 mm    |
| Length     | 92 mm    |
| Width      | 22 mm    |
| Net weight | 0.061 kg |

#### Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, Sans 21003, Kontrol Biro, EMI

#### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

|                                    |  |  |                        |
|------------------------------------|--|--|------------------------|
| Material connection 1              | Brass  | Bend radius  | 0 Millimetre           |
| Surface protection connection 1    | Untreated                                      | Outer pipe diameter connection 1                   | 16 Millimetre          |
| Surface treatment connection 1     | Untreated                                      | Outer pipe diameter connection 2                   | 12 Millimetre          |
| Material connection 2              | Copper   | Length   | 92 Millimetre          |
| Material quality connection 2      | Dezincification resistant brass (DZR)          | Length of connection 1                             | 30 Millimetre          |
| Surface protection connection 2    | Untreated                                      | Working length connection 1                        | 30 Millimetre          |
| Surface treatment connection 2     | Untreated                                      | Length of connection 2                             | 50 Millimetre          |
| Shape                              | Straight                                       | Working length connection 2                        | 50 Millimetre          |
| Reducing                           | ✘  | Wrench width                                       | 0 Millimetre           |
| Eccentric                          | ✘  | Wrench width union nut                             | 0 Millimetre           |
| System specific                    | ✓  | Tightening torque                                  | 0 0 Newtonmetre        |
| Connection 1                       | Press sleeve                                   | Medium temperature (continuous)                    | -10 70 Degrees celsius |
| Contour code connection 1          | TH   | Max. operating pressure at 20 °C                   | 16 Bar                 |
| Connection 2                       | Soldered end                                   | Max. operating pressure at max. medium temperature | 10 Bar                 |
| Contour code connection 2          | V  | Standard Dimension Ratio (SDR)                     | 0                      |
| Main colour fitting                | Grey   |  |                        |
| Material sealing                   | Ethylene-propylene diene monomer rubber (EPDM) |  |                        |
| With buffer stud                   | ✘  |  |                        |
| High tensile strength              | ✘  |  |                        |
| With thermal insulation            | ✘  |  |                        |
| Ring stiffness class               | Other  |  |                        |
| With sealing rings/gaskets         | ✘  |  |                        |
| Capped                             | ✘  |  |                        |
| With connection indicator          | ✘  |  |                        |
| With drain valve                   | ✘  |  |                        |
| With de-aerator                    | ✘  |  |                        |
| FM quality mark                    | ✘  |  |                        |
| LPCB quality mark                  | ✘  |  |                        |
| ULC quality mark                   | ✘  |  |                        |
| UL quality mark                    | ✘  |  |                        |
| DIN-CERTCO certificate             | ✘  |  |                        |
| VdS quality mark                   | ✘  |  |                        |
| With approval for TÜV              | ✘  |  |                        |
| DVGW quality mark for gas          | ✘  |  |                        |
| DVGW quality mark for water        | ✓  |  |                        |
| KIWA certified                     | ✓  |  |                        |
| Gastec QA mark                     | ✘  |  |                        |
| KOMO certified                     | ✓  |  |                        |
| Type approval according to BBR/EKS | ✘  |  |                        |