


Threefold faceplate, 71 mm centre distance, Niko Intense sterling coated

132-76700



Threefold faceplate with 71 mm centre-to-centre distance from the range Niko Intense. Niko Intense sterling coated



Technical data

Threefold faceplate, 71 mm centre distance, Niko Intense sterling coated.

- Threefold faceplate for three switches.
- Colour faceplate: sterling coated
- Colour RAL (approximately): 9007
- Colour NCS (approximately): NCS S 4000-N
- Frame composition: It is made of polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Surface treatment: coated
- Surface finishing: matt
- Coating upper frame: the upperframe is enamelled sterling
- Surface-mounting height: max. 8.5 mm
- Halogen-free: yes
- Fire safety:
 - self-extinguishing: complies with a filament test of 650°C
- Centre-to-centre distance: 71 mm
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Minimum ambient temperature: 5 °C
- Maximum ambient temperature: 40 °C
- Dimensions (HxWxD): 85 mm x 225 mm x 8.9 mm
- Certification marks: NF, KEMA, CEBEC, SEMKO, ÖVE, VDE
- Marking: EU