GLV 032-15 GOODWE ES G2

C10/26 - DECLARATION OF CONFORMITY for power-generating units GLV ed2.1.2 (12/2019)

for the application of annex D "Technical basic requirements regarding the power-generation units" of the Synergrid prescription C10/11 ed2.1 (01/09/2019)



The undersigned, Manufacturer: GoodWe Technologies Co., Ltd.
Address: No. 90 Zijin Rd., SND Suzhou, CHINA Country: CHINA

email: tao. jiang@goodwe.com
Telephone: 0086 0150 5159 0076

## the following conditions:

- 1. The power-generating unit complies with the relevant requirements set out in annex D "Technical basic requirements regarding the power-generation units" of the Synergrid prescription C10/11 ed2.1 (01/09/2019).
- 2. In order to substantiate this, a separate technical file has been submitted at least for each separate product series of the 'C10/26 list of power-generating units' of this homologation application. Each technical file shall be drawn up on the basis of a checklist Annex D, duly and correctly completed by the manufacturer, accompanied by all the required proof of conformity.
  - 2.1 For technical requirements for which the required proof of conformity (column J in checklist annex D) is a declaration of honour by the manufacturer, the manufacturer declares by signing and dating this declaration of conformity the correctness of the information (conform / not applicable) provided by him or her in columns K, L and M of this checklist.
  - 2.2. For technical requirements for which the required proof of conformity (column J in checklist Annex D) is a test report or a certificate NiAL necessary test reports and/or certificates are available \* in the technical file:
  - Certificates have been issued by an EN 45011 (or ISO 17065:2012) certification body accredited for these materials.

     Test reports have been established by an ISO 17025:2005 or ISO 17065:2012 laboratory accredited for these tests.

    file.

Done at: On:

Suzhou, China

08-11-2022

(stamp manufacturer & signature)



Homologated by Synergrid on: 10/03/2013 Stamp Synergrid SYNERGRID a.s.b.l.-v.z.w.

Galerie Ravensteingalerij 4/2 BE-1000 Bruxelles/Brussel T.V.A./B.Y.W: BE 04024958 091

\* Transition period till 01/05/2020 (see exceptions in chapter 3 of C10/11 ed 2.1 (01/09/2019)):

If at the time of submission of this homologation application it is not yet possible to submit all the necessary certificates and/or test reports (exception 3), or that the units do not yet have all the required characteristics (exceptions 1 and 2), a <u>temporary homologation</u> may be granted. All necessary certificates and/or test reports must be in the possession of Synergrid at the latest on 30/04/2020 in order to obtain a final homologation. if

	2	3	4	5	h	7	8	9	10				1				- 1	9			1	3		14	45
SYNERGRID reference number (GLVxxx-yy-zzzz)	BRAND NAME	Name of the product SERIES	REFERENCE of the model / type of the unit	FIRMWARE VERSION	ONLY for units (nuitable for) energy storage: Name and reference of the power control system		POWER		V	ADDITIONAL CHARACTERISTICS				TICS					APPLICATION				Synergrid approval date		
										D.3	1	D 4.1	0.6.2	0,7,2	0	0,7,1	D.4.3	0,9.1	£		П		T		
					power control system type EnFluRi	other power control system	P <sub>ecz</sub> rated (active) power	S <sub>max</sub> rnaximum apparent power (VA)	1-phase or 3-phase	integraled automatic separation system	"RIG type B ready" = suitable for use in installation ≥ 1MW	onal operating frequent (51,5 Hz - 52,5 Hz)	power response to underfrequency	active power reduction P(U)	compliant power control system provided (e.g. EnFluRi)	only homologated for "small power- generating installations"	only homologated for connection to HV-network	only homologated for use in module < 800W	only homologated as a backup powe system according to §2.1.1	Solar energy	CHP (combined heat & power)  Wind energy	Energy sto	Other  Backup power system	Temporary homologation (expires on 01/05/2020)	Final homologation
GLV32-15-0001	GOODWE	ES G2		000000 or higher	PAVE: Meter GM1000		3000	3000	1-phase	х			x	х	x				-	х		x	х		
GLV32-15-0002	GOODWE	ES G2		000000 ar higher	PAVE: Meter GM1000		3680	3680	1-phase	×			х	х	x					х		x :	х		
GLV32-15-0003	GOODWE	ES G2		000000 or higher	PAVE: Meter GM1000		3680	3680	1-phase	×			х	х	x					х		x :	х		
GLV32-15-0004	GOODWE	ES G2		000000 or higher	PAVE: Meter GM1000		5000	5000	1-phase	x			х	х	х					х	H	x :	x		
GLV32-15-0005	GOODWE	ES G2		000000 or higher	PAVE: Meter GM1000		5000	5000	1-phase	х			х	х	х			П		х		x :	х		
GLV32-15-0006	GOODWE	ES G2		000000 or higher	PAVE: Meter GM1000		6000	6000	1-phase	×			×	х	х					х		x :	x		
GLV32-15-0007	GOODWE	ES G2		000000 or higher	PAVE: Meter GM1000		6000	6000	1-phase	х			х	х	х					х		x :	x		
															1										
																				al,					
											_												_		
										_	-	-	_									4	-		
													_		_					-		+	-	-	
															-						+	-	+	-	
																					SYI	VE.	RG	RID a.s	
																				0	ماد		7	Www d.S	.D.IV.



## EXPLANATIONS FOR THE COMPLETION OF THE TABLE

Column	Title	Remarks
i	SYNERGRID reference number (GLVxxx-yy-zzzz)	In the case of a positive homologation, each C10/26-homologated power-generating unit is given a unique Synergrid reference number:  xxx = unique reference or the manufacturer  yy = serial number of manufacturer xxx's record xxx  zzzz = unique unit reference for the manufacturer xxx  Note : "GLV" is the internal Synergrid abbreviation for Declaration of Conformity, based on the Dutch word "Gelijkvormigheidsverklaring".
2	Brand name	Brand name under which the unit is marketed on the Bolgian market,
3	Vene of the enduct	Name of the product range.  Note: For each separate product range (or each group of units with common characteristics) a separate checklist according to Appendix D is required (sheet 3) toget with the corresponding conformity proof documents.
4	Reference of the model	Unique product name or reference. Units of the same product range must be unequivocally distinguished from each other through this name or reference.
5	Firmware version	Reference of the firmware version of the unit.
6	power control system	This case is only applicable for units (suitable for) energy starage, provided with a power control system of type EnFluR; Name and reference of the power control system of type EnFluR; compliant to the remitments in CID II add: 1 (0) (09 2019) \$4.1.7 and \$7.11.2.1
-	other power control	This case is only applicable for units (mitable tor) energy storage, provided with a power control system of monthly true than English. Name and recording of the mover control system, compliant to the requirements in C10/11 ed. 1. 101 69 2019) 47, 11, 2.2
8	Puc, rated (active)	Active (electrical) power in % at the terminals of the unit, as stated on the technical sheet / data sheet / brochure and nameplate.  Open photocoltaic inverters: see also definition in § 3.2.5 of EEC 62894 2016-11)
9	Smax - maximum apparent power (VA)	Maximum apparent (clectrical) power at the terminals of the unit, as stated on the certificate / the test report / the technical sheet / data sheet / brochure.
10	1-phase or 3-phase	Indicate whether the unit is single or three-phase. This characteristic refers to the unit itself, not to the nature of the connection to the distribution network which the unit can be connected.
П	Additional characteristics	In these columns optional additional characteristics of the units are indicated, following the information in checklist annex D and the corresponding technical file Put an "X" at each relevant additional characteristic. Note: Only units < 1 MW that are "type B ready" may be applied in an installation ≥ 1 MW (installation "type B" according to the European Network Code RfG). A unit 1 MW is only "type B ready" if it complies with all optional properties ticked in column [ of the checklist Annex D.
12	Limitations	These columns specify limitations of the units to their application in certain types of installations, in accordance with the information in the checklist in annex and the corresponding technical file.  Put an "X" to each relevant limitation.
13	Application	Indicate the applications for which the unit is suitable. Include an "X" with each application for which the unit can be used.
I M	Synergrid approval date	The series duty 6- 4- 4- 4- 4- 4- 4- 4- 4- 4- 4- 4- 4- 4-
15	Synergrid approval date Final homologation	Date on which the submitted homologation file was definitely approved by Synergrid.  A final approval will be granted as soon as Synergrid has a fully compliant homologation dossier.  A final homologation only remains valid under the following conditions:  - No changes that have an influence on the initial approval are made to (the production of) the units.  - There is no new edition of prescription CIO/11.  - The validity date of the test reports in the technical file submitted for approval has not been exceeded.  See also the general Synergrid procedure SI/OI for homologation of material, which is applicable, (1)

(1) - S1/01 Technical specification; procedure for application for homologation and renewal of homologation of materials

江湾

