

HNA-ECOLINE-SET: Basic set for Ecoline



Commercial information

The Henco Ecoline is an energy saving solution for recirculation loops, which limits heat loss between supply and return pipe. A separate pipe for the circulation water is no longer required. Designed on the Henco Super Size concept, it also combines modularity and easy installation.

* To complete the Ecoline installation you need to have a circulator and thermostatic balancing valve (not in Henco range)

One concept for all dimensions from 40 up to 75 mm!

Advantages:

- Energy saving
- Cost effective.
- Easy installation
- Less space consumption
- Anti legionellosis

Basic unit dimensions

Height	0 mm
Length	0 mm
Width	0 mm
Net weight	1.350 kg

Certificates

KIWA

Applications

Potable water, Heating, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Surface protection	Untreated	Outer pipe diameter connection 1	16 Millimetre
Surface treatment	Untreated	Outer pipe diameter connection 2	20 Millimetre
Swept entry type (with inner radius)	✓	Outer pipe diameter connection 4	0 Millimetre
Reducing	✗	Medium temperature (continuous)	-10 70 Degrees celsius
System specific	✓	Max. operating pressure at 20 °C	10 Bar
Nominal diameter connection 1	DN 8		
Connection 1	Press sleeve		
Nominal diameter connection 2	DN 10		
Connection 2	Press sleeve		
Nominal diameter connection 4	3/4 inch (20)		
Connection 4	Euroconus (expired)		
Contour code	TH		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With sealing rings/gaskets	✓		
Capped	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
KIWA certified	✓		