

## Abdeckrahmen Reinweiß glänzend



| Spezifikation                                                                                             | Bestell-Nr. | VE   | EUR/Stück o. MWSt. | PS | EAN           |
|-----------------------------------------------------------------------------------------------------------|-------------|------|--------------------|----|---------------|
|  1fach                   | 0211 112    | 1/10 | 7,77               | 01 | 4010337043973 |
|  2fach                 | 0212 112    | 1/10 | 10,67              | 01 | 4010337044017 |
|  2fach ohne Mittelsteg | 1002 112    | 1/10 | 10,67              | 01 | 4010337047094 |
|  3fach                 | 0213 112    | 1/5  | 19,47              | 01 | 4010337044031 |
|  4fach                 | 0214 112    | 1/5  | 31,45              | 01 | 4010337044055 |
|  5fach                 | 0215 112    | 1/5  | 47,99              | 01 | 4010337044079 |

### Merkmale

- Bruchsicher.
- In der Farbvariante Reinweiß glänzend: bestehend aus 85 % biozirkulärem Kunststoff.

### Technische Daten

|                       |                           |
|-----------------------|---------------------------|
| Abdeckrahmen 1f:      | B 83,3 x H 83,3 x T 10,6  |
| Abdeckrahmen 2f:      | B 83,3 x H 154,4 x T 10,6 |
| Abdeckrahmen 2f o.M.: | B 83,3 x H 154,4 x T 10,6 |

|                                                               |                           |
|---------------------------------------------------------------|---------------------------|
| Abdeckrahmen 3f:                                              | B 83,3 x H 225,9 x T 10,6 |
| Abdeckrahmen 4f:                                              | B 83,3 x H 297,2 x T 10,6 |
| Abdeckrahmen 5f:                                              | B 83,3 x H 368,5 x T 10,6 |
| Eckradius:                                                    | R 3                       |
| Biozirkulärer Kunststoff<br>- Farbvariante Reinweiß glänzend: | min. 50%                  |

---

## Hinweise

- In Verbindung mit Dichtungsflansch auch für die Montage wassergeschützt Unterputz IP44 geeignet.

---