



Color: ■ white

### Mechanical data

Suitable for male connectors

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	white
Material group	I
Insulation material (main housing)	Glass fiber-reinforced polyamide (PA66 GF)
Flammability class per UL94	V0
Fire load	0.002 MJ
Weight	0.1 g

### Commercial data

Product Group	3 (Multi Conn. System)
PU (SPU)	500 (100) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332315708
Customs tariff number	39269097900

### Product Classification

UNSPSC	39121409
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-44-04-92
ETIM 9.0	EC002848
ETIM 10.0	EC002848
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Approvals / Certificates**

**Approvals for marine applications**



Approval	Standard	Certificate Name
LR Lloyds Register	IEC 61984	96/20035 (E5)

**Downloads**

**Environmental Product Compliance**

<b>Compliance Search</b>
Environmental Product Compliance 734-130

**Documentation**

<b>Additional Information</b>			
Technical Section	03.04.2019	pdf 2027.26 KB	


**CAD/CAE-Data**

<b>CAD data</b>
2D/3D Models 734-130

<b>CAE data</b>
ZUKEN Portal 734-130

**Installation Notes**

**Coding**



Coding a male header – fitting coding key(s).  
 Black coding key(s) suitable for THR soldering process

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: [www.wago.com](http://www.wago.com)