

RANA LINEAR R 3KLM WW LOUV+PRI D
0052356



Features

- Ceiling recessed LED Linear luminaire with Louvre + Micro Prismatic Optic, Dimensions: 1154mm x 90mm x 91mm, Direct, White Body, DALI Dimmable (Switch-Dim), Warm White LED (3000K), 3200lm, 27W, 119lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse), Low LED Flicker (+/-5%), UGR<19, L90B10 at 50,000 hours, Electric Class1, Glow Wire Test 850°C, Can be covered with building insulation of Glass wool type


Product Overview

Product name	RANA LINEAR R 3KLM WW LOUV+PRI D
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Environment	Internal
Fixture luminous flux (lm)	3200
Luminaire efficacy (lm/W)	118.51
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	27
Electrical protection	Class I
Control gear type	Electronic ballast
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20


RANA LINEAR R 3KLM WW LOUV+PRI D
0052356

IK rating	IK07
Product EAN number	5410288523569
Warranty	5 years


Photometry



Technical drawings



RANA LINEAR R 3KLM WW LOUV+PRI D
0052356



Data table

GENERAL DATA

Product name	RANA LINEAR R 3KLM WW LOUV+PRI D
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Environment	Internal
Operating temperature range (°C)	-25°C...+40°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3200
Luminaire efficacy (lm/W)	118.51
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80

RANA LINEAR R 3KLM WW LOUV+PRI D 0052356

Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Glare control	< 19
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	27
Primary Supply/Product voltage - min (V)	220
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Drive current (mA)	275
Inrush Current (A)	53
Inrush Duration (µs)	300
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Connectable conductor cross section - Min (mm²)	2.5
Connectable conductor cross section - Max (mm²)	2.5

LIFETIME DATA

Lifespan L70 B50	60000
Lifespan L70 B20	60000
Lifespan L70 B10	60000
Lifespan L80 B50	60000
Lifespan L80 B20	60000
Lifespan L80 B10	60000
Lifespan L90 B50	60000
Lifespan L90 B20	60000
Lifespan L90 B10	60000

RANA LINEAR R 3KLM WW LOUV+PRI D 0052356

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Prismatic
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1150
Nominal Product Width (mm)	90
Weight (kg)	3.15
Recessed Depth (mm)	90

PACKAGING

Single packaging type	Carton
Product EAN number	5410288523569
Packaging single width (cm)	10.5
Packaging single depth (cm)	11.5
DUN14 (outer)	5410288523569
Packaging outer length / height (cm)	117.0

SAFETY DATA

Optimal operating condition (°C)	-25-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No