

## 3P-260426VK: Double Backplate elbow female short model 26x1/2"x26



### Commercial information

The body of the fitting is made from CW617N brass. These fittings offer great advantages with regard to corrosion and they are also better for the environment.

- The fitting has a buffer ring that prevents direct galvanic contact between the aluminium of the pipe and the brass of the fitting.
- This excludes the possibility of electrolysis occurring.
- The fitting is equipped with O-rings made from EPDM and RVS pressure sleeves with 3 inspection windows.
- In order to prevent assembly errors, the dimensions and type of press profile which can be pressed are shown on the RVS sleeves

### Certificates

KIWA, KOMO, AFNOR, ATG, QB (CSTBat), DNV-GL, DVGW Wasser, EMI, GOST-R, ITC, ÖN EN 21003-2/-3, ÖVGW Wasser, STF, TSU, VA (ETA), WRAS, ACS

### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary




### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Housing material	Brass	Medium temperature (continuous)	-10 70 Degrees celsius
Housing material	Brass	Max. operating pressure at 20 °C	10 Bar
Material quality	CuZn40Pb2 (CW617N)		
Surface protection	Untreated		
Shape	Right-angled		
System specific	✓		
Nominal diameter connection 2	1/2 inch (15)		
Connection	Press sleeve		
Thread size tap connection	1/2 inch		
Contour code	TH		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
Compliant with NF 545	✗		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		

## Related products

Product code	GTIN	Description	Image
BE26	05414764430662	Henco Jaws (universal) BE/TH-Profile 26x3	
PRESSCHECK1432	05414764430662	Henco Tool to control the accuracy of a pressing Ø14-32	
PLP-P-PK	05414764430662	Henco Galvanised bracket for backplate elbow	
PLF-P-PK	05414764430662	Henco Galvanised bracket flat for backplate elbow	