

## Product data sheet

Item No. 96.024.0053.0

### Male connector with strain relief RST20i2F S23YR1 V GL

Connector RST20i2, 2 pole, rectangular, male, spring clamp connection, 250V/20A, for cable diameters 6-10 mm, color of coding: light gray, color of housing: light gray



Item No.	96.024.0053.0
EAN	4049644007590
Order Unit	100 Piece(s)

#### Certificates / Approvals

#### Technical data

##### General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	
Color of housing inclusive strain relief	Light grey

##### Connection Data

Cable diameter	10 mm
Cable diameter 2	6 mm
Connection cross section solid	2.5 mm <sup>2</sup>
Cross section solid 2	0.5 mm <sup>2</sup>
Connection cross section stranded	1.5 mm <sup>2</sup>
Cross section stranded 2	0.5 mm <sup>2</sup>
Terminations per pole	2

## Model

Model	male
Number of poles	2
Connection type	Tension clamp connection
Degree of protection (IP)	IP66/IP68

## Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

## Dimensions

Length	70.5 mm
Width	34.6 mm
Height	62.3 mm

## Technical drawing

